





SPECIFICATIONS

Frequency Range: 14–14.5 GHz
 Insertion Loss: 1.4dB Max.
 Isolation: 12dB Min.
 VSWR In/Out: 1.85:1/1.75:1 Max.
 Phase Balance: ± 8 Deg. Max.
 Amplitude Balance: ± 0.3 dB Max.
 Power: 30W (Load vswr@1.2)

MATERIAL: 		MICROWAVE COMMUNICATIONS LABORATORIES INC. 7255 30TH AVE. N. SAINT PETERSBURG, FL 33710 TEL: (727) 344-6254 FAX: (727) 381-6116 http://WWW.MCLI.COM		SCALE: N/A
		SHEET: N/A		
UNLESS OTHERWISE SPECIFIED: TOLERANCES IN (INCHES) OR [mm] (MILLIMETERS) FRACTIONS: $\pm 1/64$ DECIMALS: $\pm .01 \pm .005$ ANGLE: $\pm 1/2^\circ$		DRAWING TITLE: 2-WAY POWER DIVIDER		
		PART NO. PS2-26-T/NF		
DRAWN: Paiboon Luekhamhan	DATE: 10-19-1997	PROPERTY NOTICE: THE INFORMATION IN THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT WRITTEN PERMISSION FROM MICROWAVE COMMUNICATIONS LABORATORIES INC. (MCLI)	CAGE CODE: OD2L5	SIZE: A
APPROVED: T. Nguyen	DATE: 10-19-1997	THIRD ANGLE PROJECTION 	REV: N/A	DWG NO. 80076
			DO NOT SCALE THE DRAWING	