

DESCRIPTION:

PMI MODEL NUMBER P24T-0R5G18G-60-R-SFF IS A SINGLE POLE, TWENTY-FOUR THROW REFLECTIVE SWITCH DESIGNED TO OPERATE OVER THE 500MHZ TO 18GHZ FREQUENCY RANGE. THIS MODEL IS DESIGNED TO MAINTAIN LOW INSERTION LOSS, HIGH ISOLATION, AND FAST SWITCHING SPEED.

SPECIFICATIONS:

- FREQUENCY: 0.5 GHZ TO 18.0 GHZ
- INSERTION LOSS: 7.5dB MAX.
- ISOLATION: 60dB MINIMUM
- VSWR: 2.0:1 MAX.
- SPEED: 100ns MAXIMUM
- POWER INPUT: +20dBm CW MAXIMUM
- CONTROL: 5 BIT - TTL LOGIC - SEE LOGIC TABLE
- POWER SUPPLY: +5V @ 1200mA NOMINAL
-5V @ 100mA NOMINAL
- CONNECTORS: SMA FEMALE CONNECTORS
- CONNECTORS: MICRO SUB-D 9 PIN

PIN No.	Function
1	E1
2	E2
3	E3
4	E4
5	E5
6	GND
7	+V
8	-V
9	GND

LOGIC TABLE					
5 BIT DECODER					
E1	E2	E3	E4	E5	FUNCTION
0	0	0	0	0	J1-J2 "Low Loss"
0	0	0	0	1	J1-J3 "Low Loss"
0	0	0	1	0	J1-J4 "Low Loss"
0	0	0	1	1	J1-J5 "Low Loss"
0	0	1	0	0	J1-J6 "Low Loss"
0	0	1	0	1	J1-J7 "Low Loss"
0	0	1	1	0	J1-J8 "Low Loss"
0	1	0	0	0	J1-J9 "Low Loss"
0	1	0	0	1	J1-J10 "Low Loss"
0	1	0	1	0	J1-J11 "Low Loss"
0	1	0	1	1	J1-J12 "Low Loss"
0	1	1	0	0	J1-J13 "Low Loss"



LOGIC TABLE - CONT					
5 BIT DECODER					
E1	E2	E3	E4	E5	FUNCTION
0	1	1	0	1	J1-J14 "Low Loss"
0	1	1	1	0	J1-J15 "Low Loss"
0	1	1	1	1	J1-J16 "Low Loss"
1	0	0	0	0	J1-J17 "Low Loss"
1	0	0	0	1	J1-J18 "Low Loss"
1	0	0	1	0	J1-J19 "Low Loss"
1	0	0	1	1	J1-J20 "Low Loss"
1	0	1	0	0	J1-J21 "Low Loss"
1	0	1	0	1	J1-J22 "Low Loss"
1	0	1	1	0	J1-J23 "Low Loss"
1	0	1	1	1	J1-J24 "Low Loss"
1	1	0	0	0	J1-J25 "Low Loss"

- ENVIRONMENTAL RATINGS:**
- TEMPERATURE: -55°C TO +95°C (OPERATING)
-65°C TO +125°C (STORAGE)
 - HUMIDITY: MIL-STD-202F, METHOD 103B COND. B
 - SHOCK: MIL-STD-202F, METHOD 213B COND. B
 - VIBRATION: MIL-STD-202F, METHOD 204D COND. B
 - ALTITUDE: MIL-STD-202F, METHOD 105C COND. B
 - TEMPERATURE CYCLE: MIL-STD-202F, METHOD 107

NOTE: THE ABOVE SPECIFICATIONS ARE SUBJECT TO CHANGE OR REVISION

REVISIONS		
ZONE	REV.	DESCRIPTION
	-	PRELIMINARY

DATE	APPROVED
1/11/11	



PLANAR MONOLITHICS INDUSTRIES, INC.
 7311-F GROVE ROAD
 FREDERICK, MARYLAND 21704 USA
 TEL: 301-662-5019 FAX: 301-662-1731
 WEBSITE: www.pmi-ri.com
 E-MAIL: sales@pmi-ri.com
 ISO 9001:2008 CERTIFIED



APPROVALS		DATE	TITLE
DRAWN	<i>JM</i>	1/11/11	PRODUCT FEATURE
CHECKED			
ISSUED			

SIZE	FSCM NO.	DWG NO.	REV.
A	05X00	PRELIMINARY	-

ALL DIMENSIONS ARE IN INCHES
 TOLERANCES:
 XXXX ±0.010
 XXXX ±0.005