

SPECIFICATION SHEET
JFW MODEL 50T-034-XXX
TERMINATION/MISMATCH

JFW Industries, Inc.
Phone: 317-887-1340
sales@jfwindustries.com
www.jfwindustries.com

Frequency Range	DC-1000 MHz
Impedance	50 Ohms (referenced)
Available VSWR Values	1.0:1 thru 8.0:1 in any 0.1 increment (1.0:1 = termination)
VSWR Tolerance (Termination)	1.10:1 maximum (50T-034-1.0)
VSWR Tolerance (Mismatches)	± 5% from mismatch value
RF Input Power	50 Watts average @ +25°C Derate to 25 Watts @ +85°C
Peak Power	1000 Watts
RF Connector	BNC, N, TNC, SMA or 7/16 (male or female)
Operating Temperature Range	-55°C to +100°C
Physical Size	See outline drawing 092-303

XXX - Insert VSWR value required.
Other values available upon request.

Example Model Numbers:

50T-034-1.0 N M	Termination (1.0:1) with N male
50T-034-1.5 SMA M	1.5:1 mismatch with SMA male
50T-034-3.2 TNC F	3.2:1 mismatch with TNC female
50T-034-5.0 BNC F	5.0:1 mismatch with BNC female
50T-034-5.0 7/16 M	5.0:1 mismatch with 7/16 male

ECR/ECN #	DATE	REV	APPR / DATE	ECR/ECN #	DATE	REV	APPR / DATE
9999	02/13/2003	E	SL 02/25/2003	20453	08/12/2011	J	TRS 08/12/2011
18346	03/04/2010	H	SMR 03/04/2010	20536	09/06/2011	K	TRS 09/06/2011
18459	03/24/2010	I	SMR 03/25/2010	23288	09/30/2013	L	TRS 09/30/2013