

TNC Male to BNC Female Right Angle Adapter



TECHNICAL DATA SHEET

PE9783

TNC Male to BNC Female Right Angle Adapter

Configuration

Connector 1 **TNC Male** Impedance 1 50 Ohms Connector 2 **BNC Female** 50 Ohms Impedance 2 Adapter Design Standard Body Style Right Angle Maximum Operating Voltage, Volts 500 Dielectric Withstanding Voltage, Vrms 1,500

Mechanical Specifications

Temperature

Operating Range, deg C -65 to +165

Size

 Length, in [mm]
 1.04 [26.42]

 Width/Dia., in [mm]
 0.59 [14.99]

 Height, in [mm]
 0.8 [20.32]

Connector 1

Type TNC Male
Inner Conductor Material and Plating Silver
Coupling Nut Material and Plating Brass, Nickel
Body Material and Plating Brass, Nickel
Dielectric Type PTFE

Connector 2

Type BNC Female
Inner Conductor Material and Plating Silver
Body Material and Plating Brass, Nickel
Dielectric Type PTFE

Compliance Certifications (visit www.Pasternack.com for current document)

RoHS Compliant Yes

Plotted and Other Data

Notes: Values at 25 °C, sea level

URL: http://www.pasternack.com/tnc-male-bnc-female-right-angle-adapter-pe9783-p.aspx

TNC Male to BNC Female Right Angle Adapter from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and fiber optic products maintain a 99% availability and are part of the broadest selection in the industry.

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.

ISO 9001 : 2008 Registered

PE9783 CAD DrawingTNC Male to BNC Female Right Angle Adapter

