



**Electrical Characteristics:**

1. Characteristic Impedance: 50 Ω
2. Frequency range: DC~10GHz
3. Contact resistance  
Center conductor: ≤6.0 mΩ  
Out conductor: ≤1.0 mΩ
4. Insulation resistance: ≥1000MΩ
5. Insulator withstanding: 750V
6. Durability: 5000cycles

**主要性能指标:**

1. 特性阻抗: 50 Ω
2. 频率范围: DC~10GHz
3. 接触电阻:  
中心导体: ≤6.0 mΩ  
外导体: ≤1.0 mΩ
4. 绝缘电阻: ≥1000MΩ
5. 介质耐压: 750V
6. 插拔次数: 5000次

**Application: MIL-C-39012/73A**

**执行标准: MIL-C-39012/73A**

**Material&Finishing**

1. Center contact:  
Male: phosphor bronze, gold plated
2. Bodies: brass, gold plated
3. Insulators: PTFE

**材料和镀层**

1. 中心接触件:  
插针: 锡磷青铜, 镀金
2. 壳体: 黄铜, 镀金
3. 绝缘子: 聚四氟乙烯

 	SCALE		SMC-JHD RF COAXIAL CONNECTOR	UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE mm, TOLERANCES ARE FRACTIONS DECIMALS ANGLES .X± .15 ±1° .XX± .05 .XXX±
	4:1			
	NAME	DATE		
DRAWN				
CHECKED				
APPROVED				

西安富士达科技股份有限公司  
XI'AN FORSTAR S&T CO.,LTD.