

X3 Frequency Multiplier

50Ω Output 5400 to 8100 MHz

RMK-3-812+



CASE STYLE: TT1224
PRICE: \$8.95 ea. QTY (10-49)

+RoHS Compliant

The +Suffix identifies RoHS Compliance. See our web site for RoHS Compliance methodologies and qualifications


Maximum Ratings

Operating Temperature	-40°C to 85°C
Storage Temperature	-55°C to 100°C
RF Input Power	17 dBm
Permanent damage may occur if any of these limits are exceeded.	

Pin Connections

INPUT	1
OUTPUT	4
GROUND	2,3,5,6


Outline Drawing



Outline Dimensions (inch/mm)

A	B	C	D	E	F	G	H
.25	.31	.16	.100	.040	.055	.060	.065
6.35	7.87	4.06	2.54	1.02	1.40	1.52	1.65
J	K	L	M	N	P	Q	wt.
.300	.060	.160	.025	.100	.110	.070	grams
7.62	1.52	4.06	0.64	2.54	2.79	1.78	0.16

Demo Board MCL P/N: TB-393 Suggested PCB Layout (PL-258)



- NOTES: 1. TRACE WIDTH IS SHOWN FOR ROGERS R04350B WITH DIELECTRIC THICKNESS .030" ± .002"; COPPER: 1/2 OZ. EACH SIDE. FOR OTHER MATERIALS TRACE WIDTH MAY NEED TO BE MODIFIED.
2. BOTTOM SIDE OF THE PCB IS CONTINUOUS GROUND PLANE.
3. DENOTES PCB COPPER LAYOUT WITH SMOBC (SOLDER MASK OVER BARE COPPER)
4. DENOTES COPPER LAND PATTERN FREE OF SOLDER MASK

Notes

- A. Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.
B. Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions.
C. The parts covered by this specification document are subject to Mini-Circuit's standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuit's website at www.minicircuits.com/MCLStore/terms.jsp

Features

- broadband
- high rejection F2, -40 dBc typ.; F4, -37 dBc typ.
- low cost
- aqueous washable

Applications

- synthesizers
- local oscillators
- satellite up and down converters

Electrical Specifications

MULTIPLICATION FACTOR	FREQUENCY (MHz)		INPUT POWER (dBm)		CONVERSION LOSS (dB)		*HARMONIC OUTPUT (dBC)					
	F1	F3	Min. Max.		Typ. Max.		F1	F2	F4			
	Input	Output					Typ. Min.	Typ. Min.	Typ. Min.			
3	1800-2700	5400-8100	0	6	16	21	6	-6	40	22	37	24

* Harmonics of input frequency below the power level of F3

Typical Performance Data

Input Frequency (MHz)	INPUT RF= 0 dBm				INPUT RF= 6 dBm			
	Conversion Loss (dB)	Harmonic Output Below F3 (-dBc)			Conversion Loss (dB)	Harmonic Output Below F3 (-dBc)		
		F1	F2	F4		F1	F2	F4
1800.00	19.20	4.47	41.49	31.45	18.88	9.15	44.86	36.77
1850.00	18.85	4.48	41.84	30.87	18.04	9.52	45.65	37.45
1900.00	18.34	4.62	42.52	30.79	17.25	9.92	45.56	37.91
1950.00	17.68	4.87	42.58	31.34	16.53	10.13	44.19	38.13
2000.00	17.27	4.97	42.35	31.83	16.15	10.12	43.14	37.93
2050.00	16.66	5.10	41.50	33.16	15.90	9.90	42.10	37.65
2100.00	16.45	4.90	40.15	34.10	15.78	9.58	40.97	36.70
2150.00	16.54	4.52	38.86	34.71	16.11	8.96	39.75	35.59
2200.00	16.80	3.91	38.37	35.05	16.55	8.19	38.88	34.56
2225.00	16.95	3.53	38.00	35.44	16.62	7.85	38.52	34.41
2250.00	16.67	3.61	37.71	36.23	16.59	7.69	37.98	34.86
2300.00	16.47	3.50	37.32	37.24	16.71	7.20	37.03	36.50
2350.00	16.51	3.20	36.96	37.90	17.09	6.64	35.72	41.27
2400.00	16.85	2.55	36.30	38.28	17.47	5.88	34.55	50.85
2450.00	17.27	1.92	35.49	38.87	17.87	5.23	33.71	52.34
2500.00	17.41	1.48	34.82	38.99	18.08	4.71	33.41	43.83
2550.00	17.63	1.04	33.97	39.53	18.32	4.20	33.29	40.68
2600.00	17.97	0.38	33.17	39.71	18.55	3.68	33.34	39.35
2650.00	18.07	0.10	32.34	40.50	18.75	3.29	33.51	39.50
2700.00	18.29	0.37	31.44	41.26	18.67	3.09	34.59	39.79

