



AMP1077 SOLID STATE HIGH POWER AMPLIFIER

FEATURES

Class AB linear GaN hybrid design
Instantaneous wide bandwidth
Suitable for all modulations standards
Built-in protection circuits
High reliability and ruggedness

ELECTRICAL SPECIFICATIONS

Parameter	Specification	Notes
Operating Frequency Range	2.0 - 18.0 GHz	
Power Output	5 Watt Min	CW
Power Gain	37 dB Min	
Power Gain Flatness	4.0 dB p-p Max	Constant input power
Input / Output Return Loss	10 dB Min	Relative to 50 Ohm
2-Tone Intermodulation (IMD)	>30 dBc Typ	27 dBm/Tone, $\Delta = 1$ MHz
Harmonics	>25 dBc Typ	At rated Pout
Non Harmonics Spurious	>60 dBc Min	
Noise Figure	10 dB Max	
Operating Voltage	32 VDC Nom	
Current Consumption	2.0 Amp Max	At rated Pout
Max Input Power	+10 dBm	Without damage
Load VSWR Protection	3 : 1	

ENVIRONMENTAL CHARACTERISTICS

Parameter	Specification	Notes
Operating Case Temperature	-20 to +75 °C	
Storage Temperature	-40 to +85 °C	
Relative Humidity	5 to 95 %	Non Condensation

MECHANICAL SPECIFICATIONS

Parameter	Specification	Notes
Dimensions	130 X 90 X 27 mm	Excluding Connectors
Weight	TBD	
RF Connectors In/Out	SMA female	
DC Power / Interface Connector	9-Pin D-Sub	
Cooling	External Heatsink	Forced air required

D-SUB CONNECTOR PIN ASSIGNMENT

Pin	Function	Description
1	FWD	Reserved
2	VVA	Reserved
3	CURRENT SENSOR	$I_D @ 50\text{mV}/100\text{mA Typ}$
4	TEMP SENSOR	$V_T @ 10\text{mV}/^\circ\text{C} + 500\text{mV Typ}$
5	SHUTDOWN	TTL
6, 7	VDD	32VDC
8, 9	GND	Ground

AMP1077 SOLID STATE HIGH POWER AMPLIFIER

OUTLINE DRAWING

