

SPECIFICATION SHEET
JFW MODEL 75DR-022
DUAL ROTARY ATTENUATOR

JFW Industries, Inc.
Phone: 317-887-1340
sales@jfwindustries.com
www.jfwindustries.com

Frequency Range	DC-1000 MHz
Impedance	75 Ohms nominal
Attenuation Range	0-11 dB in 0.1 dB steps
VSWR	1.4:1 maximum DC-500 MHz 1.5:1 maximum 500-1000 MHZ
Insertion Loss	1.25 dB maximum 1.00 dB typical
Attenuation Accuracy	± 0.05 dB (0.1 dB steps) ± 0.30 dB (1.0 dB steps)
RF Input Power	1 Watt average 1000 Watts peak
Direction of Rotation	Attenuation increases in a Clockwise direction
Indexing	30 degrees with stops at Minimum and maximum
RF Connector	BNC or F female
Knob/Panel Mounting Drawing	092-8435-02
Outline Drawing	092-2135 (75DR-022 BNC)

ECR/ECN #	DATE	REV	APPR / DATE	ECR/ECN #	DATE	REV	APPR / DATE
9999	05/15/2003	A		23479	11/26/2013	D	TRS 11/27/2013
20325	07/13/2011	B	TRS 07/13/2011	24023	04/16/2014	E	TRS 04/16/2014
20448	08/12/2011	C	TRS 08/12/2011	25776	09/28/2015	F	TRS 09/29/2015