

DESCRIPTION

This class AB LDMOS module is designed for both military and commercial applications. It is capable of supporting any signal type and modulation format, including but not limited to 3-4G telecom, WLAN, OFDM, DVB, and CW/AM/FM. The latest device technologies and design methods are employed to offer high power density, efficiency, and linearity in a small, lightweight package.

**FEATURES**

- Over / Under / Reverse Voltage Protection
- High Speed On/Off Control

APPLICATIONS

- Military / Commercial Data links
- Telecommunications
- BTS / Repeaters / DAS
- Test and Measurement
- General Purpose Lab Use

RF / ELECTRICAL

PARAMETER	MIN	TYP	MAX	UNIT
Operating Frequency	1350		1400	MHz
P1dB Power Output		46.0		dBm
PSat Power Output	47.0	47.5		dBm
Gain	16.0	17.0		dB
Gain Flatness		0.3	0.5	dB
OIP3		--		
OIP3 Measurement Conditions		--		--
Input Return Loss	18	20		dB
Operating Voltage	28		30	VDC
Current Draw		2.4	2.6	A
Quiescent Current Draw		0.42		A
Switching Time			200.0	nS

MECHANICAL

PARAMETER	VALUE	UNIT
Dimensions (L x W x H)	8.5x5.54x2.175	in.
RF Connectors (Input / Output)	N-F / N-F	--
DC / Control Connector	Waterproof Circular Locking	--
Cooling	Integral Heatsink – Fan options available	--
Mounting	#6 Thru-Holes	--

PARAMETER	MIN	MAX	UNIT
Operating Temp. (Housing Temp.)	-10	+80	°C
Storage Temp Range	-60	+100	°C
Weatherproofing	IP67 Equivalent		--
Altitude	0-30,000		ft.
Shock / Vibration	MIL-STD-810 and equivalents		--
Max RF Input	33.5		dBm
Load VSWR @ P1dB	Open / Short Output Protection		--
PA Baseplate Shutoff Temperature	85		°C

Technical drawing of a mechanical part, showing four views: front, top, left side, and right side. The drawing includes dimensions in inches and millimeters, and a note for hole diameter.

Front View (Top): Shows the main body with a width of 8.500 inches. The top surface has a thickness of .000 inches. The bottom surface has a thickness of .180 inches. There are three holes along the top edge, with center-to-center distances of 1.250, 4.250, and 7.250 inches. The bottom edge has a thickness of .360 inches and a hole with a diameter of $\varnothing .150(6x)$. The total height of the front view is 5.540 inches.

Top View (Bottom): Shows the top surface with a width of 9.245 inches and a height of .000 inches. The top edge has a radius of .125 inches. The bottom edge has a thickness of .000 inches.

Left Side View (Left): Shows the left side of the part with a width of 2.175 inches. The top surface has a thickness of .000 inches. The bottom surface has a thickness of .125 inches. The total height of the left side view is 5.090 inches.

Right Side View (Right): Shows the right side of the part with a width of .645 inches. The top surface has a thickness of .000 inches. The bottom surface has a thickness of .000 inches. The total height of the right side view is 4.090 inches. There are four holes along the right edge, with center-to-center distances of 1.450, 2.370, 3.170, and 4.090 inches.

DC / CONTROL PINS

PIN LABEL	NAME	DESCRIPTION
1	+VDC	Supply Voltage - Range Specified in Datasheet
2	+VDC	Supply Voltage - Range Specified in Datasheet
3	TEMP	Temp Monitor: Temp in DegC = $(V_{out} - 0.5V) / 10$
4	I/O	On / Off Control (+5V = On / 0V = Off)