




	Tolerances 1-20=+/-0.2 20-30=+/-0.3 30-40=+/-0.4 40-50=+/-0.5 50-100=+/-0.75 100-300=+/-1.5 Angles=+/-1 Dimensions are in Millimeters	Revisions	Approved	Date
		Description/Approved/Date	M.H.	03/20/99
			Checked	Date
			M.H.	03/20/99
		Drawn	Date	
		K.R.E.	03/19/99	
NOTES (plating thickness in micro-inches):		5. Per MIL-P-19468	9. Nickel pl. 100 min. over copper strike	
1. Per QQ-B-626	6. Per ZZ-R-765	7. Per WW-T-799	10. Per QQ-P-35	
2. Per QQ-S-764	8. Gold pl. 5 min. over nickel pl. 50 min. over copper strike		11. Gold pl. 5 min. over nickel pl. 50 min. over copper strike	
3. Per QQ-C-530				
4. Per QQ-B-750				



PCB FOOTPRINT RECOMMENDATION

ITEM	MATERIAL	FINISH	 Lighthouse Technologies, Inc. 5640 Kearny Mesa Road, Suite N San Diego, California 92111 Part Number: LTI-FSF55NP
Connector Body	Brass, Note 1	Tin	
Center Contact: Female	Brass, Note 1	Nickel, Note 9	
Insulation	Polypropylene	None	
Ferrule	--	--	
Gasket	--	--	
Hex Nut	--	--	
Lock Washer	--	--	
Description			Polypropylene dielectric.
F end launch PCB jack. Nickel plated bras body.			
Scale	Drawing No.	File Name	
2:1	F/FSF55	FSF55	