



50 Ohm SMA Mixer Operating From 5 GHz to 18 GHz With
an IF Range From DC to 4 GHz And LO Power of +10 dBm

TECHNICAL DATA SHEET

PE8653

50 Ohm SMA Mixer Operating From 5 GHz to 18 GHz With an IF Range From DC to 4 GHz And LO Power of +10 dBm

Configuration

Design	Double Balanced
RF Connector	SMA Female
RF Connector Impedance	50 Ohms
LO Connector	SMA Female
IF Connector	SMA Female
LO Frequency Range, GHz	DC to 4
Maximum LO Connector Power, Watts	10

Mechanical Specifications

Size

Length, in [mm]	1.55 [39.37]
Width/Dia., in [mm]	0.19 [4.83]
Height, in [mm]	0.97 [24.64]

RF Connector

Type	SMA Female
------	------------

LO Connector

Type	SMA Female
------	------------

IF Connector

Type	SMA Female
------	------------

DC Bias Connector

Type

Compliance Certifications (visit www.Pasternack.com for current document)

RoHS Compliant	Yes
----------------	-----

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [50 Ohm SMA Mixer Operating From 5 GHz to 18 GHz With an IF Range From DC to 4 GHz And LO Power of +10 dBm PE8653](#)

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.



50 Ohm SMA Mixer Operating From 5 GHz to 18 GHz With
an IF Range From DC to 4 GHz And LO Power of +10 dBm

TECHNICAL DATA SHEET

PE8653

Plotted and Other Data

Notes:

Values at 25 °C, sea level

50 Ohm SMA Mixer Operating From 5 GHz to 18 GHz With an IF Range From DC to 4 GHz And LO Power of +10 dBm from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and fiber optic products maintain a 99% availability and are part of the broadest selection in the industry.


Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [50 Ohm SMA Mixer Operating From 5 GHz to 18 GHz With an IF Range From DC to 4 GHz And LO Power of +10 dBm PE8653](http://www.pasternack.com/50-ohm-sma-mixer-5000-mhz-18000-mhz-if-dc-4000-mhz-pe8653-p.aspx)

URL: <http://www.pasternack.com/50-ohm-sma-mixer-5000-mhz-18000-mhz-if-dc-4000-mhz-pe8653-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.

PE8653 CAD Drawing

50 Ohm SMA Mixer Operating From 5 GHz to 18 GHz With an IF
Range From DC to 4 GHz And LO Power of +10 dBm



NOTES:
1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL.
2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME.
3. DIMENSIONS ARE IN INCHES [mm].

DWG TITLE
PE8653

PASTERNACK®
Pasternack Enterprises, Inc.
P.O. Box 16759 | Irvine | CA | 92623

Phone: (949) 261-1920 | Fax: (949) 261-7451
Website: www.pasternack.com | E-Mail: sales@pasternack.com

FSCM NO. 53919

CAD FILE 110111

SCALE N/A

SIZE A

2233