



50 Ohm 10 Watts Black Anodized Aluminum
Heatsink N Male RF Load Up To 6 GHz

TECHNICAL DATA SHEET

PE6185

50 Ohm 10 Watts Black Anodized Aluminum Heatsink N Male RF Load Up To 6 GHz

Configuration

Connector	N Male
Heat Sink	Black Anodized Aluminum Heatsink
Connection Method	Standard
Body Style	Straight

Electrical Specifications

Frequency Range, GHz	DC to 6
Impedance, Ohms	50
Maximum VSWR	1.15:1
Maximum Input Power, Watts	10
Peak Power, KWatts	1

Mechanical Specifications

Temperature

Operating Range, deg C	-40 to +120
------------------------	-------------

Size

Length, in [mm]	2 [50.8]
Width/Dia., in [mm]	1.1 [27.94]

Connector

Type	N Male
Inner Conductor Material and Plating	Brass, Gold
Outer Conductor Material and Plating	Brass, Tri-Metal
Coupling Nut Material and Plating	Brass, Tri-Metal
Body Material and Plating	Brass, Tri-Metal
Dielectric Type	PTFE

Compliance Certifications (visit www.Pasternack.com for current document)

RoHS Compliant	Yes
----------------	-----

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [50 Ohm 10 Watts Black Anodized Aluminum Heatsink N Male RF Load Up To 6 GHz PE6185](#)

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.



50 Ohm 10 Watts Black Anodized Aluminum
Heatsink N Male RF Load Up To 6 GHz

TECHNICAL DATA SHEET

PE6185

Plotted and Other Data

Notes:

Values at 25 °C, sea level

50 Ohm 10 Watts Black Anodized Aluminum Heatsink N Male RF Load Up To 6 GHz from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and fiber optic products maintain a 99% availability and are part of the broadest selection in the industry.


Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [50 Ohm 10 Watts Black Anodized Aluminum Heatsink N Male RF Load Up To 6 GHz PE6185](http://www.pasternack.com/10-watts-n-male-rf-load-up-to-6-ghz-pe6185-p.aspx)

URL: <http://www.pasternack.com/10-watts-n-male-rf-load-up-to-6-ghz-pe6185-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.

PE6185 CAD Drawing

50 Ohm 10 Watts Black Anodized Aluminum Heatsink N Male RF Load Up To 6 GHz



DWG TITLE

PE6185

NOTES:
1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL.
2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME.
3. DIMENSIONS ARE IN INCHES [mm].

FSCM NO. 53919

CAD FILE 040813

SCALE N/A

SIZE A

2233



Pasternack Enterprises, Inc.
P.O. Box 16759 | Irvine | CA | 92623
Phone: (949) 261-1920 | Fax: (949) 261-7451
Website: www.pasternack.com | E-Mail: sales@pasternack.com