

All components used in this assembly conform to RoHS standards.





Tolerances
 1-20=+/-0.2
 20-30=+/-0.3
 30-40=+/-0.4
 40-50=+/-0.5
 50-100=+/-0.75
 100-300=+/-1.5
 Angles=+/-1

Dimensions are in Millimeters

Revisions		Approved	Date
Description/Approval/Date	Checked	M.H.	08/05/02
	M.H.		08/05/02
	Drawn	K.R.E.	08/07/02

NOTES (plating thickness in micro-inches):

1. Per QQ-B-626	5. Per MIL-P-19468	6. Per ZZ-R-765	9. Nickel pl. 100 min. over copper strike
2. Per QQ-S-764	7. Per WW-1-799	8. Gold pl. 5 min. over nickel pl. 50 min. over copper strike	10. Per QQ-P-35
3. Per QQ-C-530			11. Gold pl. 30 min. over nickel pl. 50 min. over copper strike
4. Per QQ-B-750			



ITEM	MATERIAL	FINISH
Connector Body	Brass, Note 1	Gold, Note 8
Center Contact: Female	Phosphor Bronze, Note 4	Gold, Note 11
Insulation	Teflon, Note 5	None
Ferrule	--	--
Gasket	--	--
Hex Nut	--	--
Lock Washer	--	--

Lighthouse Technologies, Inc.
 5640 Kearny Mesa Road, Suite N
 San Diego, CA 92111
 Part Number:
LTI-7MXSF96GT

Description
 75 Ohm MCX edge mount PCB jack with solder post. Gold plated

brass body, teflon dielectric.

Scale 4:1 Drawing No. File Name 7MXSF95