

SPECIFICATION SHEET**JFW MODEL 50S-1784****1P6T SELF TERMINATING SOLID STATE RF SWITCH**

JFW Industries, Inc.
Phone: 317-887-1340
sales@jfwindustries.com
www.jfwindustries.com

Frequency Range	0.5-18 GHz
Configuration	1P6T Self Terminating
Impedance	50 Ohms nominal
VSWR	1.5:1 typical 0.5-8GHz 1.7:1 typical 8-18GHz 2.0:1 maximum 0.5-18GHz
Insertion Loss	3.0 dB typical 0.5-8GHz 3.5 dB typical 8-18GHz 4.0 dB maximum 0.5-18GHz
Isolation	90 dB typical 0.5-8GHz 80 dB typical 8-18GHz 65 dB minimum 0.5-18GHz
Switching Speed (50% TTL to 10% or 90% RF)	100 nanoseconds maximum 50 nanoseconds typical
RF Input Power	+27 dBm maximum
3rd Order Intercept Point	+45dBm minimum
Control Logic (6 Lines) (1 TTL line per port)	TTL "Low" (0-0.8V) for Insertion Loss (only one port active at a time) TTL "High" (2.0-5.0V) for OFF and Terminated
DC Supplies	+5 Vdc @ 250 mA nominal and -12 to -15 Vdc @ 50 mA nominal
DC Connector	Solder Terminals
RF Connector	SMA female
Operating Temperature Range	-55°C to +85°C
Storage Temperature Range	-65°C to +125°C
Weight	37 grams nominal
Physical Size	See outline drawing 092-8414

ECR/ECN #	DATE
	09/02/2015

REV	APPR / DATE
	BAC 09/02/2015

ECR/ECN #	DATE

REV	APPR / DATE