



Microwave Town Company, LLC

MTPA20218343402

2000MHz-18000MHz 10Watt Broadband Power Amplifier

MTPA20218343402 is a air-cooled, broadband, solid state amplifier. This rack mount amplifier based on GaN technology provides high gain, high output power, wide dynamic range, and good linearity. The front panel gain control permits the operator to conveniently set the desired output level. The LCD display shows operate status including rack temperature, current, gain, and etc. Multiple self-protection techniques are implemented such as thermal overload, excessive current flow, Input overdrive, large mismatch, fan mal-function. The status indications are available via the LCD display accordingly. This unit is suitable in EMI/EMC test, satellite communication, RF/MW measurements, and other applications.

- High Power and Efficiency
- High Reliability and Ruggedness
- Ultra Broadband
- Built-in control, monitoring & protection circuits
- GPIB option -101



ELECTRICAL CHARACTERISTICS @ 220V/110V AC, +25° C, 50Ω

PARAMETER	UNIT	MIN	TYPICAL	MAX
Frequency Response	MHz	2000		18000
Power Gain	dB		43	
Gain Flatness per 40MHz bandwidth	+/-dB		1	
Gain Flatness via Temperature	+/-dB		2	
Saturated Output Power	dBm		40	
Efficiency @ Sat Output Power	%		20	
Output Power @ 1dB gain compression point	dBm		37	
Harmonic Distortion	dBc		-20	
Spurious Signals	dBc		-60	
Load	Ohm			Infinity
IM3@P1dB	dBc		-20	
Input VSWR				2:1
Output VSWR			2:1	

Ph: (626) 823-4815

Fax: (626) 698-1638

www.MicrowaveTown.com



Microwave Town Company, LLC

MTPA20218343402

2000MHz-18000MHz 10Watt Broadband Power Amplifier

ENVIRONMENTAL SPECIFICATIONS (DESIGN TO MEET)

PARAMETER	UNIT	MIN	TYPICAL	MAX
Voltage	V (AC)		220	
Current	A		0.5	
Operating Temperature	°C	0		50
Non-Operating Temperature	°C	-40		70

MECHANICAL SPECIFICATIONS

PARAMETER	UNIT	MIN	TYPICAL	MAX
Dimensions W x H x D	Inch		12.80X19.00X2.20	
Weight	KG		10	
RF Input & Output		SMA(F), SMA(F)		
option		GPIO(101)		

PROTECTIONS

PARAMETER	UNIT	MIN	TYPICAL	MAX
Input Overdrive	dBm		+5	
Load Mismatch Tolerance			5:1 @ all phase & amplitude	
Thermal Overload	°C		85	



Microwave Town Company, LLC

MTPA20218343402

2000MHz-18000MHz 10Watt Broadband Power Amplifier

OUTLINE DRAWINGS

