


REVISIONS				
ZONE	REV	DESCRIPTION	Date	APPROVED



SPECIFICATIONS:

Frequency Range: 1.4–2.8 GHz
 Power Avg: 10 Watts
 Power Peak: 100 Watts
 Operating Temperature: 0°C to +50°C
 Isolation: 17dB Min.
 Insertion loss: 0.6dB Max.
 VSWR: 1.35:1 Max.

MATERIAL:				MICROWAVE COMMUNICATIONS LABORATORIES INC. 7255 30TH AVE. N. SAINT PETERSBURG, FL 33710 TEL: (727) 344-6254 FAX: (727) 381-6116 http://WWW.MCLI.COM		SCALE: N/A			
				UNLESS OTHERWISE SPECIFIED: TOLERANCES IN (INCHES) OR [mm] (MILLIMETERS) FRACTIONS: $\pm 1/64$ DECIMALS: $\pm 0.01 \pm 0.005$ ANGLE: $\pm 1/2^\circ$		SHEET: N/A			
DRAWN: Paiboon Luekhamhan		DATE: 04-21-2011		DRAWING TITLE: COAXIAL ISOLATOR					
APPROVED: T. Nguyen		DATE: 04-21-2011		PART NO. IS-129					
		CAGE CODE: 0D2L5		SIZE: A		REV: N/A		DWG NO. 85639	
				DO NOT SCALE THE DRAWING					