

HYBRID COUPLER

PART NO. : WVH-4X4-N-02

◆ APPLICATION

> 698MHz ~ 2,690MHz Band System

◆ FEATURE

> High Reliability
> **RoHS Compliant**

◆ ELECTRICAL SPECIFICATION

ITEM	SPECIFICATION
Frequency Range (MHz)	698 ~ 2,690
Dissipative Loss	0.3dB Max
Coupling Value	6.0dB±0.9dB
Return Loss	23.0dB Min
Isolation	25dB Min
PIMD	150dBc Min,160dBc Typ. @ 2x43dBm(2-tone)
Input Power	160W CW Max,80Watts per port
In/Out Impedance	50 Ohms Nominal

◆ ENVIRONMENTAL SPECIFICATIONS

ITEM	SPECIFICATION
Operating Temperature Range	-20°C to +70°C, IP68

◆ MECHANICAL SPECIFICATIONS

ITEM	SPECIFICATION
Dimension	150.3 x 150.3 x 28.0 Max (Unit:mm)
Mounting Points	See Outline Drawing
RF Connector	All Ports : N Female Connector
Connector Position	See Outline Drawing
Finish	Black Color Epoxy Coating Marking : White Color

HYBRID COUPLER

◆ OUTLINE DRWAING

