

SPECIFICATION SHEET

SKYFR-001303: 2620—2690 MHz Single Junction Robust Lead Isolator

Applications

- Features
- Wireless infrastructure
- Power amplifiers

• Operating frequency range: 2620 to 2690 MHz

- BeO free
- RoHS compliant



2 CCW 1

Figure 1. Block Diagram

Table 1. Absolute Maximum Ratings

Parameter	Symbol	Test Condition	Min	Max	Units
Average power, forward	P _{AVG}			40	W
Peak power, forward	Р _{РК}			150	W
Average power, reverse	P _{REV}	No time limit		30	W
Operating temperature range	T _{OP}		-40	+105	°C
Storage temperature range	TSTOR		-40	+125	°C

Note: The power rating and reliability of the device will not degrade with an operating temperature of up to +110°C. Exceeding +110°C or any of the limits listed here may result in permanent damage to the device or may reduce device reliability.

Skyworks Solutions, Inc. • Phone [781] 376-3000 • Fax [781] 376-3100 • sales@skyworksinc.com • www.skyworksinc.com Revision 2 • Skyworks Proprietary Information • Products and Product Information are Subject to Change Without Notice • Sept 2014

SPECIFICATION SHEET • SKYFR-001303

Parameter	Symbol	Test Condition	Min	Typical	Мах	Units
Frequency range	f		2620		2690	MHz
Impedance				50		Ω
Insertion loss	IL				0.30	dB
Insertion loss ripple	IL	Peak to peak			0.10	dB
Isolation	ISO		23			dB
Return loss	RL	Port 1	23			dB
Phase flatness		Peak to peak			0.5	degree
Intermodulation Distortion	IMD	2 x 15W CW tones, 1 MHz spacing	60			dBc
Harmonics					-45	dBc

Table 2. Electrical Specifications (Note 1)

Note 1: Performance is guaranteed under the conditions listed in this table and over the operating temperature range. Note 2: See Skyworks Application Note, *Intermodulation Distortion Measurements of Ferrites*, document number 201537 for further details. Note 3: Test fixture PCB: Rogers 4350B, 0.5mm thick, 50Ω line width of 1.1mm.


Table 3. Plating Specification

Section	Base Material	Plating	
Leads	Bronze	Silver	
Housing	Steel	Silver	

Table 4. Ordering Information

Manufacturing Part Number	Alternative Part Number	
SKYFR-001303	TFX-00167 (PCB-00096)	

Skyworks Solutions, Inc. • Phone [781] 376-3000 • Fax [781] 376-3100 • sales@skyworksinc.com • www.skyworksinc.com Skyworks Proprietary Information • Products and Product Information are Subject to Change Without Notice • Sept 2014



All dimensions in millimeters. Tolerance: ±0.2mm unless otherwise specified. Model number, lot code and port designation printed on top side of device.

Figure 2. Package Dimensions

Copyright © 2011 Skyworks Solutions, Inc. All Rights Reserved.

Information in the document is provided in connection with Skyworks Solutions, Inc. ("Skyworks") products or services. These materials, including the information contained herein, are provided by Skyworks as a service to its customers and may be used for information approach purposes only by the customer. Skyworks assumes no responsibility for errors or omissions in these materials or the information contained herein. Skyworks may change its documentation, products, services, specifications or product descriptions at any time, without notice. Skyworks makes no commitment to update the materials or information and shall have no responsibility whatsoever for conflicts, incompatibilities, or other difficulties arising from any future changes.

No license, whether express, implied, by estoppel or otherwise, is granted to any intellectual property rights by this document. Skyworks assumes no liability for any materials, products or information provided hereunder, including the sale, distribution, reproduction or use of any Skyworks products, information or materials, except as may be provided in Skyworks Terms and Conditions of Sale.

THE MATERIALS, PRODUCTS AND INFORMATION ARE PROVIDED "AS IS" WITHOUT WARRANTY OF ANY KIND, WHETHER EXPRESS, IMPLIED, STATUTORY, OR OTHERWISE, INCLUDING FITNESS FOR A PARTICULAR PURPOSE OR USE, MERCHANTABILITY, PERFORMANCE, QUALITY OR NON-INFRIDGEMENT OF ANY INTELLECTUAL PROPERTY RIGHT; ALL SUCH WARRANTIES ARE HEREBY EX-PRESSLY DISCLAIMED. SKYWORKS DOES NOT WARRANT THE ACCURACY OR COMPLETENESS OF THE INFORMATION, TEXT, GRAPHICS OR OTHER ITEMS CONTAINED WITHIN THESE MATERIALS. SKYWORKS SHALL NOT BE LIABLE FOR ANY DAMAGES, INCLUDING BUT NOT LIMITED TO ANY SPECIAL, INDIRECT, INCIDENTAL, STATUTORY, OR CONSEQUENCIAL DAMAGES, INCLUDING WITHOUT LIMITATION, LOST REVENUES OR LOST PROFITS THAT MAY RESULT FROM THE USE OF THE MATERIALS OR INFORMATION, WHETHER OR NOT THE RECIPIENT OF MATERIALS HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

Skyworks products are not intended for use in medical, lifesaving or life-sustaining applications, or other equipment in which the failure of the Skyworks products could lead to personal injury, death, physical or environmental damage. Skyworks customers using or selling Skyworks products for use in such applications do so at their own risk and agree to fully indemnify Skyworks for any damages resulting from such improper use or sale.

Customers are responsible for their products and applications using Skyworks products, which may deviate from published specifications as a result of design defects, errors, or operation of products outside of published parameters or design specifications. Customers should include design and operating safeguards to minimize these and other risks. Skyworks assumes no liability for applications assistance, customer product design, or damage to any equipment resulting from the use of Skyworks products outside of stated published specifications or parameters.

Skyworks, the Skyworks symbol, and "Breakthrough Simplicity" are trademarks or registered trademarks of Skyworks Solutions, Inc. in the United States and other countries. Third-party brands and names are for identification purposes only, and are the property of their respective owners. Additional information, including relevant terms and conditions, posted at www.skyworksinc.com and incorporated by reference.

Skyworks Solutions, Inc. • Phone [781] 376-3000 • Fax [781] 376-3100 • sales@skyworksinc.com • www.skyworksinc.com Skyworks Proprietary Information • Products and Product Information are Subject to Change Without Notice • Sept 2014