

## Precision SMA Female to SMP Female Adapter



## TECHNICAL DATA SHEET

PE9779

## **Precision SMA Female to SMP Female Adapter**

Configuration

Connector 1 SMA Female
Impedance 1 50 Ohms
Connector Specification 1 MIL-STD-348A
Connector 2 SMP Female
Impedance 2 50 Ohms
Adapter Design Precision
Body Style Straight

**Electrical Specifications** 

Frequency Range, GHz DC to 18
Maximum VSWR 1.2:1

**Mechanical Specifications** 

Temperature

Operating Range,deg C -65 to +125

Size

Length, in [mm] 0.76 [19.3] Width/Dia., in [mm] 0.28 [7.11]

**Connector 1** 

Type SMA Female

Inner Conductor Material and Plating Beryllium Copper, Gold Inner Conductor Plating Specification MIL-G-45204

Body Material and Plating Passivated Stainless Steel

Connector 2

Type SMP Female
Inner Conductor Material and Plating Beryllium Copper, Gold
Inner Conductor Plating Specification MIL-G-45204

Inner Conductor Plating Specification

Outer Conductor Material and Plating

Body Material and Plating

MIL-G-45204

Beryllium Copper, Gold

Passivated Stainless Steel

Compliance Certifications (visit www.Pasternack.com for current document)

RoHS Compliant Yes

**Plotted and Other Data** 

Notes: Values at 25 °C, sea level

URL: http://www.pasternack.com/sma-female-smp-female-straight-adapter-pe9779-p.aspx

Precision SMA Female to SMP Female Adapter from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and fiber optic products maintain a 99% availability and are part of the broadest

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.

ISO 9001 : 2008 Registered

**PE9779 CAD Drawing**Precision SMA Female to SMP Female Adapter

