



REVISIONS				
ZONE	REV	DESCRIPTION	DATE	APPROVED



SPECIFICATIONS

Frequency Range: 1–2 GHz
 Coupling: 10 ± 1.25 dB
 Frequency Sensitivity: ± 0.75 dB
 Insertion Loss: 0.9 dB Max.
 Directivity: 20 dB Min.
 VSWR: 1.25:1 Max.
 Power Incident, Reflected: 50W, 5W, 3kW Peak

MATERIAL:		MCLI MICROWAVE COMMUNICATIONS LABORATORIES INC. 7255 30TH AVE. N. SAINT PETERSBURG, FL 33710 TEL: (727) 344-6254 FAX: (727) 381-6116 http://WWW.MCLI.COM		SCALE: N/A
		UNLESS OTHERWISE SPECIFIED: TOLERANCES IN (INCHES) OR [mm] (MILLIMETERS) FRACTIONS: $\pm 1/64$ DECIMALS: ± 0.01 ± 0.005 ANGLE: $\pm 1/2^\circ$		SHEET: N/A
DRAWN: Paiboon Luethamhan		DRAWING TITLE: DIRECTIONAL COUPLER PART NO. C2-10/NF		
DATE: 09-27-1999		CAGE CODE: OD2L5		
APPROVED: T. Nguyen		SIZE: A REV: N/A DWG NO. 80379		
DATE: 09-27-1999		DO NOT SCALE THE DRAWING		