

# Precision 75 Ohm N Male to F Female Adapter



# TECHNICAL DATA SHEET

PE9737

# Precision 75 Ohm N Male to F Female Adapter

Connector 1N MaleImpedance 175 OhmsConnector 2F FemaleImpedance 275 OhmsAdapter DesignPrecisionBody StyleStraight

## **Electrical Specifications**

Frequency Range, GHz DC to 3
Maximum VSWR 1.3:1

#### Frequency 1

Frequency, GHz DC to 2 VSWR 1.15:1

### Frequency 2

Frequency, GHz 2 to 3 VSWR 1.3:1

#### **Mechanical Specifications**

## **Temperature**

Operating Range, deg C -65 to +125

#### Size

Length, in [mm] 1.795 [45.59] Width/Dia., in [mm] 0.8 [20.32]

## **Connector 1**

Type N Male

#### Connector 2

Type F Female

# Compliance Certifications (visit www.Pasternack.com for current document)

RoHS Compliant Yes

### **Plotted and Other Data**

Notes: Values at 25 °C, sea level

URL: http://www.pasternack.com/n-male-f-female-straight-adapter-pe9737-p.aspx

Precision 75 Ohm N Male to F Female Adapter from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and fiber optic products maintain a 99% availability and are part of the broadest selection in the industry.

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.

ISO 9001 : 2008 Registered

**PE9737 CAD Drawing**Precision 75 Ohm N Male to F Female Adapter

