

## 75 Ohm F Female Right Angle Connector Solder Attachment Thru Hole PCB, .320 inch x .091 inch Hole Spacing



## TECHNICAL DATA SHEET

PE44333

75 Ohm F Female Right Angle Connector Solder Attachment Thru Hole PCB, .320 inch x .091 inch Hole Spacing

Configuration

Connector F Female
Connector Interface Type Thru Hole
Cable Attachment Method (Shield/Contact) Solder
Body Style Right Angle

**Electrical Specifications** 

Impedance, Ohms 75

**Mechanical Specifications** 

Size

 Length, in [mm]
 1.032 [26.21]

 Width/Dia., in [mm]
 0.374 [10]

 Height, in [mm]
 0.705 [17.91]

 Weight, lbs [g]
 0.137 [62.14]

Connector

Type F Female
Contact Material and Plating Brass, Tin
Body Material and Plating Brass, Nickel
Dielectric Type Delrin/PP

Compliance Certifications (visit www.Pasternack.com for current document)

RoHS Compliant Yes

**Plotted and Other Data** 

Notes: Values at 25 °C, sea level

URL: http://www.pasternack.com/f-female-standard-thru-hole-pcb-connector-pe44333-p.aspx

75 Ohm F Female Right Angle Connector Solder Attachment Thru Hole PCB, .320 inch x .091 inch Hole Spacing from Pasternack Enterprises has same day shipment for domestic and International orders. We maintain 99% availability of the industry's broadest selection of RF, microwave and fiber optic products.

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.



## PE44333 CAD Drawing

75 Ohm F Female Right Angle Connector Solder Attachment Thru Hole PCB, .320 inch x .091 inch Hole Spacing

