

Specifications


Parameter	Unit	Min	Typical	Max
Center Frequency (F0)	MHz		160	
Bandwidth (B)	MHz		30	
Delay (T0)	μsec	10.95	11.004	11.05
Insertion Loss (IL)	dB		23	25.5
Amplitude Ripple	dB p-p		2	3
Phase Ripple	deg p-p		1.3	2.5
Spurious for $ t-T0 > .9T0$	dB		-57	-52
Substrate Material	128YX-LN			

Notes:

1. Center Frequency (F0) and Bandwidth (B) are defined, not measured.
2. Insertion Loss is the minimum loss for $|f-F0| < .5B$
3. Ripple spec applies to $|f-F0| < .4B$, and is doubled for $.4B < |f-F0| < .5B$
4. Specifications are at 22C only. Unit will operate undamaged from -54C to 125C with shifts $dF0 = -x \cdot F0$, $dT0 = x \cdot T0$, where $x = 75E-6 \cdot (\text{temperature} - 22C)$


Typical Performance

Frequency Response
(Best Fit Linear Phase Removed)




Impulse Response


FFT(Frequency Response * Cos(0.5*PI*MIN(1, MAX(0, |f-F0|*17.2/(118-8.6))))^2)



Package Outline



Matching



Matched S-parameters available at www.phonon.com