



Precision SMA Male to Mini SMP Male Adapter Full Detent

TECHNICAL DATA SHEET

PE91052

Precision SMA Male to Mini SMP Male Adapter Full Detent

Configuration

Connector 1 SMA Male Impedance 1 50 Ohms MIL-STD-348 Connector Specification 1 Connector 2 Mini SMP Male Impedance 2 50 Ohms Connector Specification 2 MIL-STD-348

Adapter Design Precision Body Style Straight

Electrical Specifications

Frequency Range, GHz DC to 26.5 Maximum VSWR 1.2:1

Mechanical Specifications

Temperature

-55 to +125 Operating Range, deg C

Size

Length, in [mm] 0.837 [21.26] Width/Dia., in [mm] 0.312 [7.92]

Connector 1

Type SMA Male Mating Cycles 100 Inner Conductor Material and Plating Beryllium Copper, Gold Inner Conductor Plating Specification MIL-G-45204, Type I, Grade 1, Class A Outer Conductor Material and Plating Passivated Stainless Steel Hex Size. Inch 5/16 Torque, in-lbs [Nm] 8 [0.9]

Body Material and Plating Passivated Stainless Steel **Body Plating Specification** AMS-QQ-P-35 Dielectric Type PTFF

Connector 2

Type Mini SMP Male

Mating Cycles 100 Inner Conductor Material and Plating Beryllium Copper, Gold Inner Conductor Plating Specification MIL-G-45204, Type I, Grade 1, Class A

Passivated Stainless Steel Body Material and Plating

PTFE Dielectric Type

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: Precision SMA Male to Mini SMP Male Adapter Full Detent PE91052

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all

ISO 9001: 2008 Registered

specifications are nominal.





Precision SMA Male to Mini SMP Male Adapter Full Detent

TECHNICAL DATA SHEET

PE91052

Compliance Certifications (visit www.Pasternack.com for current document)
RoHS Compliant
Yes

Plotted and Other Data

Notes: Values at 25 °C, sea level

Precision SMA Male to Mini SMP Male Adapter Full Detent from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and fiber optic products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: Precision SMA Male to Mini SMP Male Adapter Full Detent PE91052

URL: http://www.pasternack.com/sma-male-mini-smp-male-straight-adapter-pe91052-p.aspx

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.



PE91052 REV 1.1

PE91052 CAD DrawingPrecision SMA Male to Mini SMP Male Adapter Full Detent

