

All components used in this connector conform to RoHS standards.




**Tolerances**

- 1-20=+/-0.2
- 20-30=+/-0.3
- 30-40=+/-0.4
- 40-50=+/-0.5
- 50-100=+/-0.75
- 100-300=+/-1.5
- Angles=+/-1

Dimensions are in Millimeters

Revisions Description/Approved/Date	Approved M.H.	Date 05/19/00
	Checked M.H.	Date 05/17/00
	Drawn K.R.E.	Date 05/15/00
NOTES (plating thickness in micro-inches): 1. Per QQ-B-626 2. Per QQ-S-764 3. Per QQ-C-530 4. Per QQ-B-750 5. Per MIL-P-19468 6. Per ZZ-R-765 7. Per WW-T-799 8. Gold pl. 5 min. over nickel pl. 50 min. over copper strike 9. Nickel pl. 100 min. over copper strike 10. Per QQ-P-35 11. Gold pl. 30 min. over nickel pl. 50 min. over copper strike		

Approved by:  
Date:



RECOMMENDED  
PCB HOLE

ITEM	MATERIAL	FINISH
Connector Body	Brass, Note 1	Gold, Note 8
Center Contact: Male	Brass, Note 1	Gold, Note 11
Insulation	Teflon, Note 5	None
Ferrule	--	--
Gasket	--	--
Hex Nut	--	--
Lock Washer	--	--



Lighthorse Technologies, Inc.

5640 Kearny Mesa Road, Suite N  
San Diego, California 92111

Part Number:  
**LTI-7MXSM54GT**

Description 75 ohm MCX vertical PCB thru hole plug. Gold plated brass body, teflon dielectric.		
Scale 4:1	Drawing No. MCX/7MXSM54	File Name 7MXSM54