SPECIFICATION SHEET

JFW MODEL 50FH-XXX-100-2

100 WATT FIXED ATTENUATOR

JFW Industries, Inc.
Phone: 317-887-1340
sales@jfwindustries.com
www.jfwindustries.com

Frequency Range	DC-2000 MHz
Impedance	50 Ohms nominal
Attenuation Values	1 thru 50 dB (any 1 dB increment)
VSWR	1.3:1 maximum DC-1000 MHz 1.4:1 maximum 1000-2000 MHz
Attenuation Accuracy	± 0.5 dB
RF Input Power	100 Watts average @ 25°C Derate to 50 Watts at 85°C
Peak Power	1000 Watts (1 microsecond)
RF Connector	BNC, N, TNC, SMA, 4.1-9.5, 4.3-10.0 or 7/16
Operating Temperature Range	-55°C to +100°C
Physical Size	See outline drawing 092-136

ECR/ECN #	DATE	REV	APPR / DATE	ECR/ECN #	DATE	REV	APPR / DATE
168	08/20/1993	B		4397	12/23/2003	F	CLV 12/23/2003
781	07/30/1997	C		9999	07/03/2003	D	TRS 07/02/2003
4326	08/07/2003	E	CLV 08/07/2003	26007	12/14/2015	G	CLK 12/14/2015