

SPECIFICATION SHEET
JFW MODEL 50FHAO-XXX-75
FIXED ATTENUATOR

JFW Industries, Inc.
Phone: 317-887-1340
sales@jfwindustries.com
www.jfwindustries.com

Frequency Range	DC-3000 MHz
Impedance	50 Ohms nominal
Attenuation Values	1 thru 50 dB in any 1 dB increment
VSWR	For 1-14 dB: 1.4:1 maximum For 15-50 dB: 1.3:1 maximum
Attenuation Accuracy	± 0.5 dB
RF Input Power	75 Watts average @ +25°C
Peak Power	1000 Watts (1 microsecond pulse)
RF Connector	SMA, N, BNC, TNC, 4.1-9.5, 4.3-10.0 or 7/16
Operating Temperature Range	-55°C to +100°C
Physical Size	See outline drawing 092-3836

ECR/ECN #	DATE	REV	APPR / DATE	ECR/ECN #	DATE	REV	APPR / DATE
9999	07/28/2003	B	SL 04/06/2004	20288	07/01/2011	E	TRS 07/01/2011
18119	01/15/2010	C	SMR 01/15/2010	20424	08/03/2011	F	TRS 08/05/2011
19004	08/13/2010	D	TRS 08/13/2010	26007	12/14/2015	G	CLK 12/14/2015