


REVISIONS				
ZONE	REV	DESCRIPTION	DATE	APPROVED



SPECIFICATIONS:

Frequency Range: 2-4 GHz

Isolation: 18dB Min.

Insertion loss: 0.50 dB Max.

VSWR: 1.35:1 Max.

Power Avg/Peak: 1 Watt / 100W

Operating Temperature: -30°C TO +70°C

MATERIAL:		MICROWAVE COMMUNICATIONS LABORATORIES INC. 7255 30TH AVE. N. SAINT PETERSBURG, FL 33710 TEL: (727) 344-6254 FAX: (727) 381-6116 http://WWW.MCLI.COM		SCALE: N/A
DRAWN: Paiboon Luekhamhan DATE: 11-15-2011		DRAWING TITLE: COAXIAL CIRCULATOR		SHEET: N/A
APPROVED: T. Nguyen DATE: 11-15-2011		PART NO. CS-10-1		
DRAWING NOTES: THE INFORMATION IN THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT WRITTEN PERMISSION FROM MICROWAVE COMMUNICATIONS LABORATORIES INC. (MCLI)		THIRD ANGLE PROJECTION	CAGE CODE: 0D2L5	SIZE: A REV: A DWG NO. 84600
		DO NOT SCALE THE DRAWING		