

TECHNICAL DATA SHEET

4 Section Bandpass Filter With SMA Female Connectors Operating From 2.5 GHz To 2.7 GHz With a 200 MHz Passband





**PE8712** 

## 4 Section Bandpass Filter With SMA Female Connectors Operating From 2.5 GHz To 2.7 GHz With a 200 MHz Passband

Configuration	
Configuration Design	Combline Filter
Connector 1	SMA Female
Connector 2	SMA Female
Passband Frequency Range, GHz	2.5 to 2.7
Electrical Specifications	
Passband Minimum Frequency, GHz	2.5
Passband Maximum Frequency, GHz	2.7
Impedance, Ohms	50
Maximum Insertion Loss, dB	1
Passband Maximum VSWR	1.5:1
Maximum Input Power, Watts Rejection at 1.7 GHz	5 50 dB
Rejection at 3.5 GHz	50 dB
Rejection at 5.5 GHz	50 UB
Mechanical Specifications	
Connector 1	
Туре	SMA Female
Connector 2	
Туре	SMA Female

Compliance Certifications (visit www.Pasternack.com for current document) RoHS Compliant Yes

## **Plotted and Other Data**

Notes:


Values at 25 °C, sea level

URL: http://www.pasternack.com/4-section-band-pass-filter-2.5-ghz-2.7-ghz-passband-200-mhz-pe8712-p.aspx

4 Section Bandpass Filter With SMA Female Connectors Operating From 2.5 GHz To 2.7 GHz With a 200 MHz Passband from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and fiber optic products maintain a 99% availability and are part of the broadest selection in the industry.

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.

Pasternack Enterprises, Inc. • P.O. Box 16759, Irvine, CA 92623 **Phone:** (866) 727-8376 or (949) 261-1920 • **Fax:** (949) 261-7451 Sales@Pasternack.com • Techsupport@Pasternack.com



PE8712 CAD Drawing 4 Section Bandpass Filter With SMA Female Connectors Operating

From 2.5 GHz To 2.7 GHz With a 200 MHz Passband

