

180 to 300MHz – Dual Junction Coaxial Isolator

Design Features

- ◆ Can be dual junction even three for high isolation.
- ◆ Military, space and commercial applications.
- ◆ Guaranteed for one year standard.
- ◆ High RF performance, ultra-competitive price.
- ◆ Custom design available upon request.

RF Characteristics


Model Number	Freq. Range (MHz)	Insertion Loss (1-2) Max(dB)	Isolation (2-1) Min(dB)	VSWR Max	Forward Power(W)	Reverse Power(W)	Connector Type	Temp.(°C)
UIYCDC10457A180T210NF	180 ~ 200	1.4	36	1.3	300	300	N-F	-20 ~ +65
UIYCDC10457A1975T2075NF	197.5 ~ 207.5	1.2	40	1.25	300	300	N-F	-20 ~ +65
UIYCDC10457A200T210NFTTAB	200 ~ 210	1.0	40	1.25	300	300	N-F to TAB	-20 ~ +65
UIYCDC10457A210T250NM	210 ~ 250	1.6	36	1.3	300	300	N-M	-20 ~ +65
UIYCDC10457A250T280SF	250 ~ 280	1.0	40	1.25	100	100	SMA-F	-20 ~ +65
UIYCDC10457A265T275SF	265 ~ 275	0.8	40	1.2	100	100	SMA-F	-30 ~ +70
UIYCDC10457A360T400NF	360 ~ 400	0.7	50	1.2	300	300	N-F	-30 ~ +70
UIYCDC10457A400T430NF	400 ~ 430	0.6	50	1.2	300	300	N-F	-30 ~ +70
UIYCDC10457A400T470NF	400 ~ 470	0.7	45	1.2	300	300	N-F	-30 ~ +70
UIYCDC10457A430T470NF	430 ~ 470	0.6	50	1.2	300	300	N-F	-30 ~ +70

² List are specify frequency range and other ranges available.

² Please enter below information when inquiry and mark * is must.

- * 1. The specific frequency range
- * 2. Power handling (Forward, Reverse, Peak, etc.)
- * 3. Connect type (SMA Male/ Female, N Male/ Female, etc.)
- 4. Other special request if have (Insertion Loss, Isolation, VSWR, Temperature, Dimension, etc.)

Mechanical Drawing



Unit: mm/ inch, General part tolerance is ± 0.2 mm unless otherwise stated.

Ver. 5

A2-5G, Zhujiang Plaza, Longxiang Blvd, Longgang District, Shenzhen 518172, China.

Tel: +86-755-25999990 25999909 Fax: +86-755-25999959 E-mail: sales@uiy.com Web: www.uiy.com