



Pigtail Test Probe Cable SMA Female to Pre-Trimmed Lead Using PE-034SR Coax, RoHS

RF Cable Assemblies Technical Data Sheet


PE3CA1105

Configuration

- Connector 1: SMA Female
- Connector 2: Pre-Trimmed Lead
- Cable Type: PE-034SR

Features

- 100% RF Tested prior to final trim
- 1.35 Max VSWR to 6 GHz
- 100% High Pot Tested to 500V
- .034 Diameter Semi Rigid coax
- Individually packed in protective tube



Applications

- Used as an RF Test Probe to 6 GHz
- RF PCB board measurements
- Signal injection

Description

These SMA Female to pre-trimmed cables assemblies are designed to be used as convenient test probes. The pre-trimmed end of the cable assembly has an exposed center conductor and dielectric and is ready for use. A common Research and development application is to solder the trimmed end of the cable to an exposed microstrip trace to inject a signal or to measure a signal of interest. Each cable assembly is individually packaged in a reusable protective tube. These test probes have been 100% RF tested as a two ended assembly prior to trimming in order to verify the assemblies perform to 6 GHz with a maximum VSWR of 1.35:1. Flush Cutt Test Probes are also available.

Electrical Specifications

| Description | Minimum | Typical | Maximum | Units |
|------------------------|---------|---------|---------|-------|
| Frequency Range | DC | | 6 | GHz |
| VSWR | | | 1.35:1 | |
| Operating Voltage (AC) | | | 500 | Vrms |

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [Pigtail Test Probe Cable SMA Female to Pre-Trimmed Lead Using PE-034SR Coax, RoHS PE3CA1105](#)



Pigtail Test Probe Cable SMA Female to Pre-Trimmed Lead Using PE-034SR Coax, RoHS

RF Cable Assemblies Technical Data Sheet

PE3CA1105

Specifications by Frequency

| Description | F1 | F2 | F3 | F4 | F5 | Units |
|-----------------------|--------|--------|----|----|----|--------|
| Frequency | 1 | 6 | | | | GHz |
| Insertion Loss (Max.) | 0.48 | 1.1 | | | | dB/ft |
| | [1.57] | [3.61] | | | | [dB/m] |
| VSWR (Max.) | 1.35:1 | 1.35:1 | | | | |

Mechanical Specifications

Cable Assembly

Cable

| | |
|--------------------------------------|---------------------------|
| Cable Type | PE-034SR |
| Impedance | 50 Ohms |
| Inner Conductor Type | Solid |
| Inner Conductor Material and Plating | Copper Clad Steel, Silver |
| Dielectric Type | PTFE |
| Number of Shields | 1 |
| Jacket Material | Copper, Tan |
| Jacket Diameter | 0.034 in [0.86 mm] |

Connectors

| Description | Connector 1 | Connector 2 |
|--------------------------------------|-------------|------------------|
| Type | SMA Female | Pre-Trimmed Lead |
| Impedance | 50 Ohms | 50 Ohms |
| Outer Conductor Material and Plating | Brass, Gold | |
| Body Material and Plating | Brass, Gold | |

Environmental Specifications

Temperature

| | |
|-----------------|------------|
| Operating Range | +125 deg C |
|-----------------|------------|

Compliance Certifications (visit www.Pasternack.com for current document)

| | |
|----------------|-----|
| RoHS Compliant | Yes |
|----------------|-----|

Plotted and Other Data

Notes:

- Values at 25°C, sea level.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [Pigtail Test Probe Cable SMA Female to Pre-Trimmed Lead Using PE-034SR Coax, RoHS PE3CA1105](#)



Pigtail Test Probe Cable SMA Female to Pre-Trimmed Lead Using PE-034SR Coax, RoHS

RF Cable Assemblies Technical Data Sheet

PE3CA1105

How to Order

Part Number Configuration:

PE3CA1105

- **xx**

uu

Unit of Measure:
cm = Centimeters
<blank> = Inches
Length
Base Number

Example: PE3CA1105-12 = 12 inches long cable
PE3CA1105-100cm = 100 cm long cable

Pigtail Test Probe Cable SMA Female to Pre-Trimmed Lead Using PE-034SR Coax, RoHS from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99% availability and are part of the broadest selection in the industry.


Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [Pigtail Test Probe Cable SMA Female to Pre-Trimmed Lead Using PE-034SR Coax, RoHS PE3CA1105](http://www.pasternack.com/sma-female-terminated-lead-sexless-pe-034sr-cable-assembly-pe3ca1105-p.aspx)

URL: <http://www.pasternack.com/sma-female-terminated-lead-sexless-pe-034sr-cable-assembly-pe3ca1105-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.

PE3CA1105 CAD Drawing

Pigtail Test Probe Cable SMA Female to Pre-Trimmed Lead Using PE-034SR Coax, RoHS



NOTES:
1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL.
2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME.
3. DIMENSIONS ARE IN INCHES [mm].
4. LENGTH TOLERANCE IS $\pm 1.5\%$ OR $3/8"$, WHICHEVER IS GREATER.

DWG TITLE
PE3CA1105

FSCM NO. 53919

CAD FILE 050815

SCALE N/A

SIZE A

2233

PE PASTERNAK®
THE ENGINEER'S RF SOURCE
Pasternack Enterprises, Inc.
P.O. Box 16759 | Irvine | CA | 92623
Phone: (949) 261-1920 | Fax: (949) 261-7451
Website: www.pasternack.com | E-Mail: sales@pasternack.com