

50 Ohm 2 Watts Brass N Male RF Load Up To 4 GHz



TECHNICAL DATA SHEET

PE6154

50 Ohm 2 Watts Brass N Male RF Load Up To 4 GHz

_	•	4.
1.0	ntin	IIPATIAN
CU	IIIIu	uration

Connector Design Standard
Connector N Male

Electrical Specifications

Frequency Range, GHz DC to 4
Impedance, Ohms 50
Maximum VSWR 1.1:1
Maximum Input Power, Watts 2

Mechanical Specifications

Temperature

Operating Range, deg C -30 to +80

Size

Length, in [mm] 0.83 [21.08] Width/Dia., in [mm] 0.82 [20.83]

Connector

Type N Male
Inner Conductor Material and Plating Brass, Gold
Outer Conductor Material and Plating Brass, Nickel
Coupling Nut Material and Plating Brass, Nickel
Body Material and Plating Brass, Nickel
Dielectric Type Teflon

Compliance Certifications (visit www.Pasternack.com for current document)

Plotted and Other Data

Notes: Values at 25 °C, sea level

URL: http://www.pasternack.com/2-watts-n-male-rf-load-up-to-4-ghz-pe6154-p.aspx

50 Ohm 2 Watts Brass N Male RF Load Up To 4 GHz from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and fiber optic products maintain a 99% availability and are part of the broadest selection in the industry.

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.



PE6154 CAD Drawing 50 Ohm 2 Watts Brass N Male RF Load Up To 4 GHz

