



REVISIONS				
ZONE	REV	DESCRIPTION	DATE	APPROVED

4X  $\phi$ .118 [ $\phi$ 3.00] THRU

6X SMA FEMALE

**SPECIFICATIONS**  
 Frequency Range: 800–2500 MHz  
 Insertion Loss: 10dB Max.  
 Isolation: 20dB Min.  
 Power Rating: 50 Watts  
 Impedance: 50 Ohms  
 VSWR: 1.30:1 Max.  
 Operating Temperature: -35°C to +55°C

MATERIAL:		MICROWAVE COMMUNICATIONS LABORATORIES INC. 7255 30TH AVE. N. SAINT PETERSBURG, FL 33710 TEL: (727) 344-0254 FAX: (727) 351-0110 <a href="http://www.mcli.com">http://www.mcli.com</a>		SCALE: N/A
UNLESS OTHERWISE SPECIFIED: TOLERANCES IN (INCHES) OR (mm) (MILLIMETERS) FRACTIONS: $\pm 1/64$ DECIMALS: $\pm 0.03 \pm 0.015$ ANGLE: $\pm 1/2^\circ$		DRAWING TITLE: <b>5-WAY POWER DIVIDER</b>		
DRAWN: Paboon Luethamhan		DATE: 09-26-2006		PART NO.: PM5-114
APPROVED: T. Nguyen		DATE: 09-26-2006		SIZE: OD2L5
				REVISION: N/A
				DWG NO.: 82659
DO NOT SCALE THE DRAWING				