



WR-42 Standard Gain Horn Antenna Operates From 18 GHz to 26.5 GHz With a Maximum 0 dB Gain WR-42 Input

TECHNICAL DATA SHEET

PE9852-15

Configuration

Design WR-42 Standard Gain Horn Frequency Range, GHz 18 to 26.5

Polarization Linear Interface 1 WR-42

Electrical Specifications

Nominal Gain, dB

Mechanical Specifications

Size

 Length, in [mm]
 2.37 [60.2]

 Width, in [mm]
 1.22 [30.99]

 Height, in [mm]
 0.92 [23.37]

Compliance Certifications (visit www.Pasternack.com for current document)

Plotted and Other Data

2 Dimensional OML Drawing PE9852-15

Notes: Values at 25 °C, sea level

WR-42 Standard Gain Horn Antenna Operates From 18 GHz to 26.5 GHz With a Maximum 0 dB Gain WR-42 Input from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and fiber optic products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: WR-42 Standard Gain Horn Antenna Operates From 18 GHz to 26.5 GHz With a Maximum 0 dB Gain WR-42 Input PE9852-15

URL: http://www.pasternack.com/standard-gain-horn-waveguide-size-wr42-pe9852-15-p.aspx

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.



PE9852-15 CAD Drawing

WR-42 Standard Gain Horn Antenna Operates From 18 GHz to 26.5 GHz With a Maximum 0 dB Gain WR-42 Input

