



ISSUE 1; September 2014 - RoHS 2011/65/EU

Description

- Intended for applications requiring shock survivability to 10,000G (and higher), the surface-mount CXOXHG oscillator is a high-shock version of the CXOX oscillator. This oscillator consist of a CMOS compatible hybrid circuit and a state-of-the-art fundamental-mode crystal.
- SM1 Gold Plated (RoHS)
- SM5 Solder Dipped (RoHS)

Frequency Parameters

- Frequency 1.0MHz to 160.0MHz
- Frequency Tolerance $\pm 100.00\text{ppm}$
- Tolerance Condition @ 25°C
- Frequency Stability $\pm 50.00\text{ppm}$ to $\pm 100.00\text{ppm}$
- Ageing $\pm 5\text{ppm}$ max in 1st year

Electrical Parameters

- Supply Voltage 5.0V $\pm 10\%$
- Supply Current Typical:
8mA @ 24MHz
10mA @ 32MHz
13mA @ 50MHz
39mA @ 130MHz
- Supply Voltage (absolute maximum rating): -0.5V to 7V

Operating Temperature Ranges

- 10 to 70°C
- 40 to 85°C
- 55 to 125°C

Output Details



- Output Compatability CMOS
- Drive Capability 15pF
- Start Up Time: 5ms max

Environmental Parameters

- Shock: 10000G, 0.3ms, 1/2 sine
- Vibration: MIL-STD-202G, Method 204D, Condition D: 20G rms, 10Hz-2000Hz swept sine
- Storage Temperature Range: -55 to 125°C




Outline (mm)



Underside View

Pad Connections	Height (H) =
1. NC/EN	SM1 1.09 max
2. GND	SM3 1.21 max
3. Output	SM5 1.21 max
4. +Vs	

Solder Pad Layout



Sales Office Contact Details:

UK: +44 (0)1460 270200
Germany: +49 (0) 30 408 192 300

France: +33 (0)5 34 50 91 18
USA: +1 408.273.4530

Email: info@iqdfrequencyproducts.com
Web: www.iqdfrequencyproducts.com

Manufacturing Details

- Features:
 - High shock resistance
 - Low acceleration sensitivity
 - Low power consumption
 - Low EMI emission
 - Optional Output Enable/Disable with Tri-State
 - Full military testing available
- Applications:
 - Military & Aerospace -
 - Smart munitions
 - Communications
 - Navigation
 - GPS
 - Industrial, Computer & Communications -
 - Miniature clock oscillator
 - Handheld instrumentation
 - PDA
 - Transponder/Animal migration
 - Medical -
 - Test & Diagnostic equipment
 - Handheld devices
- Solder Process Temperature: 260°C max for 20sec max

Ordering Information

- Frequency*
Model*
Termination Variant*
Output
Frequency Tolerance (@ 25°C)*
Frequency Stability*
Operating Temperature Range*
Pad 1 Function*
(*minimum required)
- Termination Variants:
SM1 = Gold Plated / SM5 = Solder Dipped
(Note: Non-RoHS compliant terminations also available - SM3 = Solder Dipped)
- Example
40.0MHz CXOXHG 5.0V SM1
CMOS ±100ppm ±100ppm -40 to 85C NC

Compliance

- | | |
|------------------------------|----------------|
| ■ RoHS Status | Optional |
| ■ REACH Status | Compliant |
| ■ MSL Rating (JDEC-STD-033): | Not Applicable |

Packaging Details

- | | |
|--------------------|--|
| ■ Pack Style: Tray | Supplied on a tray |
| Pack Size: 1 | |
| ■ Pack Style: Reel | Tape & reel in accordance with EIA-481-D |
| Pack Size: 1,000 | |

Sales Office Contact Details:

UK: +44 (0)1460 270200
Germany: +49 (0) 30 408 192 300

France: +33 (0)5 34 50 91 18
USA: +1 408.273.4530

Email: info@iqdfrequencyproducts.com
Web: www.iqdfrequencyproducts.com

**Electrical Specification - maximum limiting values 5.0V $\pm$ 10%**

Frequency Min	Frequency Max	Temperature Range	Stability (min)	Current Draw	Rise and Fall Time	Duty Cycle
		°C	ppm	mA	ns	%
1.0MHz	160.0MHz	-10 to 70	$\pm$ 50.0	-	6	40/60
		-40 to 85	$\pm$ 100.0	-	6	40/60
		-55 to 125	$\pm$ 100.0	-	6	40/60

This document was correct at the time of printing; please contact your local sales office for the latest version.

[Click to view latest version on our website.](#)

Sales Office Contact Details:

UK: +44 (0)1460 270200

France: +33 (0)5 34 50 91 18

Email: info@iqdfrequencyproducts.com

Germany: +49 (0) 30 408 192 300

USA: +1 408.273.4530

Web: www.iqdfrequencyproducts.com