Low Pass Filter

LFCN-123+

DC to 12000 MHz 50Ω

The Big Deal

- •Small size 3.2mm x 1.6mm
- •Pass band (DC-12000 MHz)
- •Low Insertion Loss (2.0 dB typical)
- Sharp rejection peaks close to stop band



CASE STYLE: FV1206-4

Product Overview

The LFCN-123+ Low Pass Filter gives microwave communication system designers the ability to reject unwanted harmonics using defined RF parameters. The multilayer construction gives high repeatability of performance. Small wrap-around terminations minimize variations in performance due to parasitics. Covering DC-12000 MHz, these units offer low insertion loss and good rejection.

Key Features

Feature	Advantages
Small Size (3.20mm x1.6 mm)	Allows for high layout density of circuit boards, while minimizing affects of parasitics.
Rejection peaks at harmonic frequencies	Provides good rejection of signals at harmonic frequencies, for improved system performance.
Wrap around termination	Provides excellent solderability and easy visual inspection capability.
LTCC construction	Provides a rugged package that is well suited for tough environments including high humidity and high temperature extremes.

A. Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.

B. Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions.

C. The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms_isp

Low Pass Filter

LFCN-123+

 50Ω

DC⁽¹⁾ to 12000 MHz

Maximum Ratings

Operating Temperature	-55°C to 100°C
Storage Temperature	-55°C to 100°C
RF Power Input*	8W max. at 25°C
DC Current Input to Output	0.5A max. at 25°C


^{*} Passband rating, derate linearly to 3W at 100°C ambient. Permanent damage may occur if any of these limits are exceeded.


Pin Connections

RF IN	1
RF OUT	3
GROUND	2,4

Product Marking: AP

Outline Drawing






Outline Dimensions (inch)

J	Н	G	F	Е	D	С	В	Α
.069	.104	.182	.012	.075	.026	.037	.063	.126
1.75	2.64	4.62	0.30	1.91	0.66	0.94	1.60	3.20
wt		R	Q	Р	N	M	L	K
grams		.039	.020	.024	.013	.039	.041	.119
.020		0.99	0.51	0.61	0.33	0.99	1.04	3.02

Demo Board MCL P/N: TB-618 Suggested PCB Layout (PL-363)



NOTE: 1. TRACE WIDTH IS SHOWN FOR ROGERS RO4350B
WITH DIELECTRIC THICKNESS .010" ± .001".
COPPER: 1/2 OZ. EACH SIDE.
FOR OTHER MATERIALS TRACE WIDTH MAY NEED
TO BE MODIFIED.
2. BOTTOM SIDE OF THE POB IS CONTINUOUS GROUND PLANE.
DENOTES POB COPPER LAYOUT WITH SMOBC (SOLDER
MASK OVER BARE COPPER)

DENOTES COPPER LAND PATTERN FREE OF SOLDER MASK

Features

- excellent power handling, 8W
- small size, 0.12" x .06"
- 7 sections
- temperature stable
- hermetically sealed
- LTCC construction
- protected by U.S. Patent 6,943,646

Applications

- harmonic rejection
- VHF/UHF transmitters/receivers
- lab use

Electrical Specifications(1,2) at 25°C

CASE STYLE: FV1206-4 PRICE: \$1.99 ea. QTY (20)

+RoHS Compliant The +Suffix identifies RoHS Compliance. See our web site

	Available Tape and Reel at no extra cost	
Reel Size	Devices/Reel	

for RoHS Compliance methodologies and qualifications


Reel Size	Devices/Reel
7"	20, 50, 100, 200, 500,1000, 300

Parameter		F#	Frequency (MHz)	Min.	Тур.	Max.	Unit
	Insertion Loss	DC-F1	DC - 12000	_	_	2.5	dB
Pass Band (See Typical Performance Data)	Freq. Cut-Off	F2	13000	_	3.0	_	dB
	VSWR	DC-F1	DC - 12000	_	1.6	_	:1
Stop Band	Dejection Lass	F3	15000	20	_	_	dB
	Rejection Loss	F4-F5	15500 - 20000	_	40	_	dB
	VSWR	F3-F6	15500 - 20000	_	17	_	-1

- (1) In Application where DC voltage is present at either input or output ports, coupling capacitors are required.
- (2) Measured on Mini-Circuits Characterization Test Board TB-618.


Electrical Schematic






Typical Performance Data at 25°C

	• •	
Frequency (MHz)	Insertion Loss (dB)	VSWR (:1)
10.00	0.07	1.00
1280.00	0.31	1.44
1550.00	0.39	1.55
2080.00	0.51	1.70
3140.00	0.48	1.61
4200.00	0.26	1.05
5000.00	0.48	1.61
5330.00	0.62	1.76
6260.00	0.73	1.85
8450.00	0.77	1.92
10070.00	1.07	1.87
11020.00	0.78	1.29
12010.00	1.23	1.70
13220.00	3.56	2.12
15120.00	38.92	67.22
17710.00	43.82	57.85
20000.00	39.95	78.02





A. Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.

B. Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions.

C. The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms_isp