




Absorptive 0.5 -4GHz Coaxial SP2T Switch



Features

- Wide Band Operation 0.5-4GHz
- High Power Handle Capability up to 5W upon request.
- TTL compatible driver include
- Fast Switching Speed
- Low Insertion Loss and High Isolation
- Temperature Range -45°C~+85°C
- Customization available upon request

Specification	Absorptive type		
	PN: RFSP2TA0004G		
	Low	Med	High
Frequency Range(GHz)	0.5	2.25	4
Insertion Loss(dB)	0.5dB typ. @0.5GHz	0.6dB typ. @2.25GHz	1.0dB typ. @4GHz
VSWR	1.5	1.4	1.5
Isolation(dB)	65	65	60
Switching Speed(ns)	50	100	150
P1dB Power (dBm)		24	
Absolutely max. Power (W)			1
Weight (g)	25		
IIP3 (Input IP3) dBm	42.92		
Impedance(Ohms)	50Ω		
Power Supply (V)	+/-5 V DC		
Current(mA)	80mA (+5V) 30mA (-5V)		
Input Connector	SMA-Female		
Output Connector	SMA-Female		
Finishing	Gold Plating		
Material	Brass		
Seal	Hermetically Sealed		
Control (TTL Driver Included)	TTL Control		
	TTL	Status	
	0	J0-J2	
	1	J0-J1	

Absorptive Coaxial Single Pole Double Throw Switch 0.5-4GHz



RF-LAMBDA

The power beyond expectations

RFSP2TA0004G

Absolute Maximum Ratings	
Biasing	+/-5 V
TTL Control Voltage	+5V/0V
Input RF power	+30dBm
Storage Temperature (C°)	-54 to 125°C


Biasing Up Procedure	
Step 1	-5V
Step 2	+5V
Step 3	TTL
Power OFF Procedure	
Step 1	+5V
Step 2	-5V
Step 3	TTL

Environment specifications	
Operational Temperature (C°)	-45 ~ +85°C
Storage Temperature (C°)	-54 to 125°C
Altitude	30,000 ft (Controlled environment)
Vibration	25g rms (15 degree 2KHz)
Humidity	100% RH at 35c, 95%RH at 40 deg c
Shock	20G for 11msc

Ordering Information		
Part No	ECCN	Description
RFSP2TA0004G	EAR99	SP2T 0.5-4GHz PIN Diode Switch



Median Lifetime (Tm) vs. Channel Temperature (Tch)



Absorptive Coaxial Single Pole Double Throw Switch 0.5-4GHz









RF-LAMBDA

The power beyond expectations

RFSP2TA0004G

Absorptive Coaxial Single Pole Double Throw Switch 0.5-4GHz






RF-LAMBDA

The power beyond expectations




RFSP2TA0004G

1dB Compression Point



Date: 7.OCT.2012 14:32:31

IP₃ – INPUT IP₃ Point



Important Notice

The information contained herein is believed to be reliable. RF-Lambda makes no warranties regarding the information contained herein. RF-Lambda assumes no responsibility or liability whatsoever for any of the information contained herein. RF-Lambda assumes no responsibility or liability whatsoever for the use of the information contained herein. The information contained herein is provided "AS IS, WHERE IS" and with all faults, and the entire risk associated with such information is entirely with the user. All information contained herein is subject to change without notice. Customers should obtain and verify the latest relevant information before placing orders for RF-Lambda products. The information contained herein or any use of such information does not grant, explicitly or implicitly, to any party any patent rights, licenses, or any other intellectual property rights, whether with regard to such information itself or anything described by such information.

RF-Lambda products are not warranted or authorized for use as critical components in medical, life-saving, or life sustaining applications, or other applications where a failure would reasonably be expected to cause severe personal injury or death.

Absorptive Coaxial Single Pole Double Throw Switch 0.5-4GHz