

DESCRIPTION

PMI MODEL P1T-DC40G-65-T-292MF-1NS-OPT27G IS AN ABSORPTIVE, SINGLE POLE, SINGLE THROW PIN DIODE SWITCH THAT OPERATES FROM 50 MHz TO 27 GHZ. THIS MODEL INCORPORATES A TTL COMPATIBLE DRIVER FOR EASY SYSTEM INTEGRATION.

SPECIFICATIONS

- FREQUENCY RANGE: 50 MHz to 27GHz
- ISOLATION: 65 dB Typical, 55 dB Min.
- INSERTION LOSS: 5.5 dB Typical, 6.8 dB Max.
- VSWR IN / OUT: 2.0:1 Typical, 2.2:1 Max.
- INPUT POWER: +17 dBm CW MAX
- SWITCHING SPEED: 5 ns Typical, 6 ns Max.
- RISE/FALL TIME: 0.9 ns Typical, 1 ns Max.
- CONTROL SIGNAL: TTL "1" = ON
- DC VOLTAGE: +8 to +15V @ 15mA Max.
-8 to -15V @ 40mA Max.
- CONNECTORS IN/OUT: 2.92mm MALE/FEMALE CONNECTORS
- CONTROL CONNECTORS: SMC
- FINISH: BLUE EPOXY POLIMIDE COATING IAW MIL-C-22750, TYPE I OVER EPOXY POLIMIDE PRIMER IAW MIL-P-23377, TYPE I, CLASS 1 OR 3.
- SIZE: 1.2" X 1.3" X 0.5"


ENVIRONMENTAL RATINGS

- TEMPERATURE: -40°C TO +85°C (OPERATING)
-55°C TO +125°C (STORAGE)
- HUMIDITY: MIL-STD-202F, METHOD 103B COND. B
- SHOCK: MIL-STD-202F, METHOD 213B COND. B
- VIBRATION: MIL-STD-202F, METHOD 204D COND. B
- ALTITUDE: MIL-STD-202F, METHOD 105C COND. B
- TEMPERATURE CYCLE: MIL-STD-202F, METHOD 107

NOTE: SPECIFICATIONS WILL VARY OVER OPERATING TEMPERATURE
NOTE: THE ABOVE SPECIFICATIONS ARE SUBJECT TO CHANGE OR REVISION

REVISIONS				
ZONE	REV.	DESCRIPTION	DATE	APPROVED
	1	ORIGINAL RELEASE	04/30/15	

MECHANICAL OUTLINE



PMI CONFIDENTIAL AND PROPRIETARY

PLANAR MONOLITHICS INDUSTRIES, INC.

7311-F GROVE ROAD
FREDERICK, MARYLAND 21704 USA
TEL: 301-662-5019 FAX: 301-662-1731
WEBSITE: www.pmi-rf.com
E-MAIL: sales@pmi-rf.com
ISO 9001 CERTIFIED



ALL DIMENSIONS ARE IN INCHES
TOLERANCES:
X.XX ±0.020
X.XXX ±0.010

APPROVALS		DATE		TITLE			
DRAWN		04/30/15		PRODUCT FEATURE			
CHECKED				P1T-DC40G-65-T-292MF-1NS-OPT27G			
ISSUED				SIZE	FSCM NO.	DWG NO.	REV.
				A	05XQ0	27025512	1
				SCALE	N:S	SHEET	1 OF 1