

PART NO. : WVC-3484B-20M02

◆ APPLICATION

> for 3474MHz ~ 3494MHz Band System

◆ FEATURE

> High Reliability
> **RoHS Compliant**

◆ ELECTRICAL SPECIFICATION

ITEM	SPECIFICATION
Frequency Range	3474MHz ~ 3494MHz
Insertion Loss	3.8dB Max
Return Loss	15.0dB Min
Group Delay Variation	50nS Max
Attenuation	30dB Min @ DC ~ 3440MHz 36dB Min @ 3440MHz ~ 3466MHz 30dB Min @ 3466MHz ~ 3469MHz 30dB Min @ 3499MHz ~ 3600MHz
In/Out Impedance	50 Ohms nominal
Power Handling(CW)	2W CW Max

◆ ENVIRONMENTAL SPECIFICATIONS

ITEM	SPECIFICATION
Operating Temperature	-40°C to +85°C

◆ MECHANICAL SPECIFICATIONS

ITEM	SPECIFICATION
Dimension	180.0 x 65.0 x 23.0 (Unit : mm)
Mounting Points	See Outline Drawing
RF Connector	SMA Female Connector
Connector Position	See Outline Drawing
Painting	Black Color Epoxy Coating

◆ OUTLINE DRAWING

