

SPECIFICATION SHEET**JFW MODEL 75R-006****ROTARY ATTENUATOR**

JFW Industries, Inc.
Phone: 317-887-1340
sales@jfwindustries.com
www.jfwindustries.com

Frequency Range	DC-500 MHz
Impedance	75 Ohms nominal
Attenuation Range	0-1 dB in 0.1 dB steps
VSWR	1.3:1 maximum
Insertion Loss	0.7 dB maximum
Attenuation Accuracy	± 0.02 dB DC-300 MHz ± 0.03 dB 300-500 MHz
RF Input Power	1 Watt average 1000 Watts peak
Direction of Rotation	Attenuation increases in a Counter-Clockwise direction
Indexing	30 degrees with stops at minimum and maximum
RF Connector	BNC or F female
Knob/Panel Mounting Drawing	092-8435-03
Outline Drawings	092-002-01 (75R-006 BNC) 092-002-02 (75R-006 F)

ECR/ECN #	DATE	REV	APPR / DATE	ECR/ECN #	DATE	REV	APPR / DATE
476	10/30/1995	A		17378	07/02/2009	D	TRS 07/02/2009
9999	05/15/2003	B	BAC 06/21/2007	17479	07/28/2009	E	TRS 07/28/2009
14521	08/07/2007	C	TRS 08/07/2007	25779	09/29/2015	F	TRS 09/29/2015