



产品型号 type	L	L1	L2
SMA-KFD392	41.2	15.5	2.0
SMA-KFD417	38.0	12.5	1.5

Electrical Characteristics:

1. Characteristic Impedance: 50Ω
2. Frequency range: DC~18GHz
3. Contact resistance
Center conductor: $\leq 3.0 \text{ m}\Omega$
Out conductor: $\leq 2.0 \text{ m}\Omega$
4. Insulation resistance: $\geq 5000 \text{ M}\Omega$
5. Insulator withstanding: 1000V
6. Durability: 500cycles

Application: MIL-C-39012/55D

Material & Finishing

1. Center contact :
Female: beryllium, gold plated
2. Body: Brass, gold plated
3. Insulators: PTFE

主要性能指标:

1. 特性阻抗: 50Ω
2. 频率范围: DC~18GHz
3. 接触电阻:
中心导体: $\leq 3.0 \text{ m}\Omega$
外导体: $\leq 2.0 \text{ m}\Omega$
4. 绝缘电阻: $\geq 5000 \text{ M}\Omega$
5. 介质耐压: 1000V
6. 插拔次数: 500次

执行标准: MIL-C-39012/55D

材料和镀层

1. 中心接触件:
插孔: 铍青铜, 镀金
2. 壳体: 黄铜, 镀金
3. 绝缘子: 聚四氟乙烯

 	SCALE	
	2.5:1	
	NAME	DATE
DRAWN		
CHECKED		
APPROVED		

SMA-KFD392
RF COAXIAL CONNECTOR

UNLESS OTHERWISE SPECIFIED
DIMENSIONS ARE mm, TOLERANCES ARE
FRACTIONS DECIMALS ANGLES
.X± .15 ±1°
.XX± .05
.XXX±

西安富士达科技股份有限公司
XI'AN FORSTAR S&T CO.,LTD.