

产品型号 type	备注 remark
SMA-KK1	
SMA-KK1G	不锈钢壳体 bodies, stainless steel

Electrical Characteristics

- Characteristic Impedance: $50\ \Omega$
- Frequency range: DC~18Ghz
- Contact resistance
Center conductor: $\leq 3.0\ m\Omega$
Out conductor: $\leq 2.0\ m\Omega$
- Insulation resistance: $\geq 5000M\ \Omega$
- Insulator withstanding: 1000V
- VSWR: ≤ 1.25
- Durability: 500cycles

Application: MIL-C-39012/55D

Material&Finishing

- Center contact :
Female: beryllium coper. gold plated
- Body: brass, gold plated
- Insulators: PTFE


主要性能指标

- 特性阻抗: $50\ \Omega$
- 频率范围: DC~18Ghz
- 接触电阻:
中心导体: $\leq 3.0\ m\Omega$
外导体: $\leq 2.0\ m\Omega$
- 绝缘电阻: $\geq 5000M\ \Omega$
- 介质耐压: 1000V
- 电压驻波比: ≤ 1.25
- 插拔次数: 500次

执行标准: MIL-C-39012/55D

材料和镀层

- 中心接触件:
插孔: 镀青铜, 镀金
- 壳体: 黄铜, 镀金
- 绝缘子: 聚四氟乙烯

	SCALE		SMA-KK1 RF COAXIAL CONNECTOR	UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE mm, TOLERANCES ARE FRACTIONS DECIMALS ANGLES .X± .15 ±1° .XX± .05 .XXX±
	2.5:1			
DRAWN	NAME	DATE	西安富士达科技股份有限公司 XI'AN FORSTAR S&T CO.,LTD.	
CHECKED				
APPROVED				