





Electrical Characteristics:

1. Characteristic Impedance: $50\ \Omega$
2. Frequency range: DC~18Ghz
3. Contact resistance
Center conductor: $\leq 3.0\ m\Omega$
Out conductor: $\leq 2.0\ m\Omega$
4. Insulation resistance: $\geq 5000M\Omega$
5. Insulator withstanding: 1000V
6. Durability: 500cycles

Application: MIL-C-39012/55D

Material&Finishing

1. Center contact :
Female: beryllium copper, gold plated
2. Body: brass, gold plated
3. Insulators: PTFE


主要性能指标:

1. 特性阻抗: $50\ \Omega$
2. 频率范围: DC~18Ghz
3. 接触电阻:
中心导体: $\leq 3.0\ m\Omega$
外导体: $\leq 2.0\ m\Omega$
4. 绝缘电阻: $\geq 5000M\Omega$
5. 介质耐压: 1000V
6. 插拔次数: 500次

执行标准: MIL-C-39012/55D

材料和镀层

1. 中心接触件:
插孔: 铍青铜, 镀金
2. 壳体: 黄铜, 镀金
3. 绝缘子: 聚四氟乙烯

	SCALE	
	4:1	
	NAME	DATE
DRAWN		
CHECKED		
APPROVED		

SMA-KHD6
RF COAXIAL CONNECTOR

UNLESS OTHERWISE SPECIFIED
DIMENSIONS ARE mm, TOLERANCES ARE
FRACTIONS DECIMALS ANGLES
.X± .15 ±1°
.XX± .05
.XXX±

西安富士达科技股份有限公司
XI'AN FORSTAR S&T CO.,LTD.