

MHV Female to SHV Plug Adapter



TECHNICAL DATA SHEET

PE9265

MHV Female to SHV Plug Adapter

Configuration

Connector 1MHV FemaleConnector 2SHV PlugAdapter DesignStandardBody StyleStraight

Electrical Specifications

Impedance, Ohms 50

Mechanical Specifications

Temperature

Operating Range,deg C -65 to +165

Size

 Length, in [mm]
 1.95 [49.53]

 Width/Dia., in [mm]
 0.57 [14.48]

 Dielectric Type
 PTFE

Connector 1

Type MHV Female
Inner Conductor Material and Plating Silver
Inner Conductor Plating Specification QQ-S-365
Body Material and Plating Brass, Nickel

Connector 2

Type SHV Plug
Inner Conductor Material and Plating Silver
Inner Conductor Plating Specification QQ-S-365
Body Material and Plating Brass, Nickel

Compliance Certifications (visit www.Pasternack.com for current document)

RoHS Compliant Yes

Plotted and Other Data

Notes: Values at 25 °C, sea level

URL: http://www.pasternack.com/mhv-female-shv-plug-straight-adapter-pe9265-p.aspx

MHV Female to SHV Plug Adapter from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and fiber optic products maintain a 99% availability and are part of the broadest selection in the industry.

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.

ISO 9001 : 2008 Registered

PE9265 CAD Drawing

MHV Female to SHV Plug Adapter

