

Coaxial Cavity Band Pass Filter 2510-2540MHz



Features

- High Rejection
- Low Insertion Loss
- Excellent Temperature Stability
- Miniaturization
- Filter Type: Cavity
- Customization available upon request

Electrical Specifications, TA = +25 ° C, 50 Ohm System,

Parameters		Min.	Тур.	Max.	Units
Center Frequency			2525		MHz
Band width		30			MHz
Insertion Loss			0.6	1.0	dB
Pass Band Ripple				0.5	dB
VSWR			1.2	1.3	
Rejection	@± 60MHz off center	45	50		dB
Power Rating	Average			30	w
	Perk			0.3	ĸw
Operating Temperature		-25		+70	°C
Impedance		50			Ohms
Weight		4.23			ounces
Input / Output Connector		N-Female			
Material		Aluminum			
Finishing		Gray Paint			




Environment specifications

•				
Operational				
Temperature (C°)	-25 to +70			
Storage				
Temperature (C°)	40 to +105			
	30,000 ft. (Epoxy Seal Controlled environment)			
Altitude	60,000 ft 1.0psi min (Hermetically Seal Un-controlled environment) (Optional)			
Vibration	25g rms (15 degree 2KHz) endurance, 1 hour per axis			
Humidity	100% RH at 35c, 95%RH at 40 deg c			
Shock	20G for 11msc half sin wave,3 axi both directions			


Typical performance plots

Loss VS. Ripple VS. Rejection VS. VSWR



Outline Drawing:

All Dimensions in mm (inches)



Important Notice

The information contained herein is believed to be reliable. RF-Lambda makes no warranties regarding the information contained herein. RF-Lambda assumes no responsibility or liability whatsoever for any of the information contained herein. RF-Lambda assumes no responsibility or liability whatsoever for the use of the information contained herein. The information contained herein is provided "AS IS, WHERE IS" and with all faults, and the entire risk associated with such information is entirely with the user. All information contained herein is subject to change without notice. Customers should obtain and verify the latest relevant information before placing orders for RF-Lambda products. The information contained herein or any use of such information does not grant, explicitly or implicitly, to any party any patent rights, licenses, or any other intellectual property rights, whether with regard to such information itself or anything described by such information.

RF-Lambda products are not warranted or authorized for use as critical components in medical, life-saving, or life sustaining applications, or other applications where a failure would reasonably be expected to cause severe personal injury or death.