

SMA Female to TNC Female 4 Hole Flange Adapter



TECHNICAL DATA SHEET

PE9276

SMA Female to TNC Female 4 Hole Flange Adapter

Configuration

Connector 1 SMA Female
Connector Specification 1 MIL-STD-348
Connector 2 TNC Female
Connector Specification 2 MIL-STD-348
Adapter Design Standard
Body Style Straight
Mount Method 4 Hole Flange

Electrical Specifications

Impedance, Ohms 50

Mechanical Specifications

Temperature

Operating Range,deg C -65 to +165

Size

 Length, in [mm]
 1.012 [25.7]

 Width/Dia., in [mm]
 0.687 [17.45]

 Height, in [mm]
 0.687 [17.45]

Dielectric Type PTFE

Connector 1

Type SMA Female

Inner Conductor Material and Plating Beryllium Copper, Gold

Inner Conductor Plating Specification MIL-G-45204
Body Material and Plating Brass, Nickel

Connector 2

Type TNC Female
Inner Conductor Material and Plating Gold
Inner Conductor Plating Specification MIL-G-45204
Body Material and Plating Brass, Nickel

Compliance Certifications (visit www.Pasternack.com for current document)

RoHS Compliant Yes

Plotted and Other Data

Notes: Values at 25 °C, sea level

URL: http://www.pasternack.com/sma-female-tnc-female-straight-adapter-pe9276-p.aspx

SMA Female to TNC Female 4 Hole Flange Adapter from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and fiber optic products maintain a 99% availability and are part of the broadest selection in the industry.

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.

ISO 9001 : 2008 Registered

PE9276 CAD DrawingSMA Female to TNC Female 4 Hole Flange Adapter

