

产品型号 type	配接电缆 cable type
L29-J534	LDF4-50A(HELIAX ANDREW)

Electrical Characteristics:

- Characteristic Impedance: 50 Ω
- Frequency range: DC~6Ghz
- Contact resistance
Center conductor: ≤1.0 mΩ
Out conductor: ≤0.5 mΩ
- Insulation resistance: ≥10000MΩ
- Insulator withstanding: 4000V
- VSWR: ≤1.5
- Durability: 500cycles

主要性能指标:

- 特性阻抗: 50 Ω
- 频率范围: DC~6Ghz
- 接触电阻:
中心导体: ≤1.0 mΩ
外导体: ≤0.5 mΩ
- 绝缘电阻: ≥10000MΩ
- 介质耐压: 4000V
- 电压驻波比: ≤1.5
- 插拔次数: 500次

Application: IEC 60169-4


执行标准: IEC 60169-4

Material & Finishing

材料和镀层

- Center contact:
Male: phosphor bronze, silver plated
- Out conductor: brass, silver plated
Other metal parts: brass, nickel plated
- Insulators: PTFE
- Gasket: silicone rubber

- 中心接触件:
插针: 锡磷青铜, 镀银
- 外导体: 黄铜, 镀银
其它金属零件: 黄铜, 镀镍
- 绝缘子: 聚四氟乙烯
- 密封圈: 硅橡胶

	SCALE	UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE mm, TOLERANCES ARE FRACTIONS DECIMALS ANGLES .X± .15 ±1° .XX± .05 .XXX±
	1.5:1	
	NAME	DATE
L29-J534 RF COAXIAL CONNECTOR		
西安富士达科技股份有限公司 XI'AN FORSTAR S&T CO.,LTD.		
DRAWN		
CHECKED		
APPROVED		