


剥线尺寸
stripping dimension



产品型号 type	配接电缆 cable type
DSD-KB3	SFT-50-3-1、RG402/U

Electrical Characteristics:

- Characteristic Impedance: $50\ \Omega$
- Frequency range: DC~2.0GHz
- Contact resistance
Center conductor: $\leq 5.0\ m\Omega$
Out conductor: $\leq 2.0\ m\Omega$
- Insulation resistance: $\geq 500M\Omega$
- Insulator withstanding: 500V
- VSWR: ≤ 1.3
- Durability: 500cycles

主要性能指标:

- 特性阻抗: $50\ \Omega$
- 频率范围: DC~2.0GHz
- 接触电阻:
中心导体: $\leq 5.0\ m\Omega$
外导体: $\leq 2.0\ m\Omega$
- 绝缘电阻: $\geq 500M\Omega$
- 介质耐压: 500V
- 电压驻波比: ≤ 1.3
- 插拔次数: 500次

Application: Q/FD20131-2006

执行标准: Q/FD20131-2006

Material&Finishing

- Center contact :
Female: beryllium copper, gold plated
- Body: brass, gold plated
- Insulators: PTFE

材料和镀层

- 中心接触件:
插孔: 铍青铜, 镀金
- 壳体: 黄铜, 镀金
- 绝缘子: 聚四氟乙烯

 		SCALE		DSD-KB3	UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE mm, TOLERANCES ARE FRACTIONS DECIMALS ANGLES .X± .15 ±1° .XX± .05 .XXX±
		2.5:1			
	NAME	DATE	RF COAXIAL CONNECTOR		
DRAWN					
CHECKED					
APPROVED					
					西安富士达科技股份有限公司 XI'AN FORSTAR S&T CO.,LTD.

西安富士达科技股份有限公司
XI'AN FORSTAR S&T CO.,LTD.