



Electrical Characteristics:

1. Characteristic Impedance: 50 Ω
2. Frequency range: DC~11Ghz
3. Contact resistance
Center conductor: ≤1.0 mΩ
Out conductor: ≤0.2 mΩ
4. Insulation resistance: ≥5000MΩ
5. Insulator withstanding: 1500V
6. Durability: 500cycles

主要性能指标:

1. 特性阻抗: 50 Ω
2. 频率范围: DC~11Ghz
3. 接触电阻:
中心导体: ≤1.0 mΩ
外导体: ≤0.2 mΩ
4. 绝缘电阻: ≥5000MΩ
5. 介质耐压: 1500V
6. 插拔次数: 500次

Application: MIL-C-39012/1E

执行标准: MIL-C-39012/1E

Material & Finishing

1. Center contact:
brass, gold plated
2. Bodies and other metal parts:
brass, nickel plated
3. Insulators: PTFE
4. Gasket: silicone rubber

材料和镀层

1. 中心接触件:
黄铜, 镀金
2. 壳体和其它金属零件:
黄铜, 镀镍
3. 绝缘子: 聚四氟乙烯
4. 密封圈: 硅橡胶

 	SCALE	UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE mm, TOLERANCES ARE FRACTIONS DECIMALS ANGLES .X± .15 ±1° .XX± .05 .XXX±
	1.5:1	
	N-JKE	<p style="text-align: center;">RF COAXIAL CONNECTOR</p> <p style="text-align: center;">西安富士达科技股份有限公司 XI'AN FORSTAR S&T CO.,LTD.</p>
	RF COAXIAL CONNECTOR	
DRAWN		
CHECKED		
APPROVED		