





This document contains proprietary information and such information may not be disclosed to others for any purposes, nor used for sales/marketing/procurement purposes without written permission

本文件包含专有信息，没有书面许可，该信息不能以任何形式披露给第三方，也不能用于任何目的的买卖、销售及采购。



安装开孔
mounting hole



Electrical Characteristics:

- 1.Characteristic Impedance: 50 Ω
- 2.Frequency range: DC~2Ghz
- 3.Contact resistance
Center conductor: $\leq 6.0 \text{ m}\Omega$
Out conductor: $\leq 2.0 \text{ m}\Omega$
4. Insulation resistance: $\geq 10000 \text{ M}\Omega$
5. Insulator withstanding: 750V
6. Durability: 500cycles

Application: DIN 41626

Material&Finishing

- 1.Center contact :
Female:beryllium copper, gold plated
2. Body:brass, gold plated
3. Insulators:PTFE

主要性能指标:

1. 特性阻抗: 50 Ω
2. 频率范围: DC~2Ghz
3. 接触电阻:
中心导体: $\leq 6.0 \text{ m}\Omega$
外导体: $\leq 2.0 \text{ m}\Omega$
4. 绝缘电阻: $\geq 10000 \text{ M}\Omega$
5. 介质耐压: 750V
6. 插拔次数: 500次

执行标准: DIN 41626

材料和镀层

1. 中心接触件:
插孔: 铍青铜, 镀金
2. 壳体: 黄铜, 镀金
3. 绝缘子: 聚四氟乙烯

		SCALE	
		2.5:1	
	NAME	DATE	
DRAWN			
CHECKED			
APPROVED			

DSB-KWHD
RF COAXIAL CONNECTOR

UNLESS OTHERWISE SPECIFIED
DIMENSIONS ARE mm, TOLERANCES ARE
FRACTIONS DECIMALS ANGLES
.X $\pm$.15 $\pm 1^\circ$
.XX $\pm$.05
.XXX $\pm$

西安富士达科技股份有限公司
XI'AN FORSTAR S&T CO.,LTD.